


CM-Series Hydraulic Couplings

Features


- Interchangeable with Foster® Series-FJT, Hansen® Flo-Temp, Tomco® MC-Series, DME® Jiffy-Tite, and Parker® Moldmate
- Contact Dixon® for pressure ratings and other technical information

Specification

- Silicone gaskets and valve O-rings standard providing a temperature range -90°F to 400°F (-68°C to 205°C)



steel



brass

Industrial Mold Plug Female NPTF

Body Size	Threads	Steel Part #	Brass Part #
1/4"	1/8" – 27 NPTF	CM2F1	CM2F1-B
	1/4" – 18 NPTF	CM2F2	CM2F2-B
	3/8" – 18 NPTF	CM2F3	CM2F3-B
3/8"	1/4" – 18 NPTF	CM3F2	CM3F2-B
	3/8" – 18 NPTF	CM3F3	CM3F3-B
1/2"	1/2" – 14 NPTF	---	CM4F4-B
	3/4" – 14 NPTF	---	CM4F6-B

Industrial Mold Plug Male NPTF

Body Size	Threads	Brass Part #
1/4"	1/8" – 27 NPTF	CM2M1-B
	1/4" – 18 NPTF	CM2M2-B
	3/8" – 18 NPTF	CM2M3-B
3/8"	1/4" – 18 NPTF	CM3M2-B
	3/8" – 18 NPTF	CM3M3-B
	1/2" – 14 NPTF	CM3M4-B
1/2"	1/2" – 14 NPTF	CM4M4-B
	3/4" – 14 NPTF	CM4M6-B

Industrial Mold Extension Plug Male NPTF

Body Size	Threads	Brass Part #
1/4"	1/8" – 27 NPTF	CM2M1-B-L2.5
		CM2M1-B-L4
		CM2M1-B-L5.5
	1/4" – 18 NPTF	CM2M2-B-L2.5
		CM2M2-B-L4
		CM2M2-B-L5.5
3/8"	1/8" – 27 NPTF	CM2M2-B-L7
		CM3M1-B-L2.5
		CM3M1-B-L4
		CM3M1-B-L5.5
		CM3M1-B-L7
		CM3M1-B-L11.5
	1/4" – 18 NPTF	CM3M2-B-L2.5
		CM3M2-B-L4
		CM3M2-B-L5.5
		CM3M2-B-L7
		CM3M2-B-L8.5
		CM3M2-B-L11.5

