


Hydraulic Adapters – O-ring Boss® (ORB)

Specification Male x Female NPTF

- Pressure rating at 70°F (21°C)




Male SAE O-ring Boss	Female NPTF Pipe	PSI	Zinc Plated Steel Part #
7/16" – 20	1/8" – 27	5000	6405-4-2
	1/4" – 18		6405-4-4
	3/8" – 18		6405-4-6
9/16" – 18	1/4" – 18	4000	6405-6-4
	3/8" – 18		6405-6-6
	1/2" – 14		6405-6-8
3/4" – 16	3/8" – 18	4000	6405-8-6
	1/2" – 14		6405-8-8
7/8" – 14	1/4" – 18	3000	6405-10-4
	1/2" – 14		6405-10-8
	3/4" – 14		6405-10-12
1-1/16" – 12	1/2" – 14	3000	6405-12-8
	3/4" – 14	2500	6405-12-12
	1" – 11-1/2	2000	6405-12-16
1-5/16" – 12	3/4" – 14	2500	6405-16-12
	1" – 11-1/2	2000	6405-16-16
	1-1/4" – 11-1/2	1150	6405-16-20
1-5/8" – 12	1" – 11-1/2	2000	6405-20-16
	1-1/4" – 11-1/2	1150	6405-20-20

90° Male SAE x Male JIC Elbows

Specifications

- Reference SAE 070220
- Pressure rating at 70°F (21°C)



Male SAE O-ring Boss	Male JIC	PSI	Zinc Plated Steel Part #
7/16" – 20	7/16" – 20	5000	1238-04-04
	9/16" – 18		1238-04-06
9/16" – 18	7/16" – 20	5000	1238-06-04
	9/16" – 18		1238-06-06
3/4" – 16	9/16" – 18	4500	1238-08-06
	3/4" – 16		1238-08-08
	7/8" – 14		1238-08-10
7/8" – 14	3/4" – 16	3500	1238-10-08
	7/8" – 14		1238-10-10
	1-1/16" – 12		1238-10-12
1-1/16" – 12	7/8" – 14	3500	1238-12-10
	1-1/16" – 12		1238-12-12
	1-5/16" – 12		1238-12-16
1-5/16" – 16	1-1/16" – 12	3000	1238-16-12
1-5/16" – 12	1-5/16" – 12	3000	1238-16-16
1-5/8" – 12	1-5/16" – 12		1238-20-16
1-5/8" – 12	1-5/8" – 12	2500	1238-20-20
	1-7/8" – 12		1238-24-24

90° SAE x Female NPSM Swivel Nut Elbows

Specifications

- Reference SAE 140257
- Pressure rating at 70°F (21°C)



Male SAE O-ring Boss	Female NPSM Swivel	PSI	Zinc Plated Steel Part #
7/16" – 20	1/4" – 18	4500	6901-4-4
	3/8" – 18		6901-4-6
9/16" – 18	1/4" – 18	4000	6901-6-4
	3/8" – 18		6901-6-6
	1/2" – 14		6901-6-8
3/4" – 16	3/8" – 18	3500	6901-8-6
	1/2" – 14	4000	6901-8-8
	3/4" – 14	3000	6901-8-12
7/8" – 14	1/2" – 14	3500	6901-10-8
	3/4" – 14	3000	6901-10-12
	1/2" – 14	3500	6901-12-8
1-1/16" – 12	3/4" – 14	3000	6901-12-12
	1" – 11-1/2	2500	6901-12-16
	3/4" – 14	3000	6901-16-12
1-5/16" – 12	1" – 11-1/2	2500	6901-16-16
	1-1/4" – 11-1/2	2000	6901-16-20
	1-5/8" – 12		6901-20-20