



NOTE(S):

- 1) MAX OPERATING PRESSURE: 125 PSI @ AMBIENT TEMPERATURE
- 2) FLANGE DIMENSIONS PER ANSI B16.5
- 3) CAM AND GROOVE ADAPTER PRODUCED TO INTERCHANGE WITH ALL PRODUCTS PRODUCED TO COMMERCIAL ITEM DESCRIPTION A-A-59326E



The Right Connection™

[dixonvalve.com](http://dixonvalve.com)

**PROPRIETARY AND CONFIDENTIAL**

This drawing is owned by Dixon Valve & Coupling Co. and shall be returned upon demand. It is loaned on condition that it shall not be copied or reproduced or submitted to others without the owners consent. In accepting it subject to this condition the recipient further agrees that this drawing or any design detail or concept disclosed herein shall not be used in any way detrimental to or in competition with the owner. If the recipient does not agree to the terms of this agreement they shall return this drawing immediately. The information contained in this drawing is subject to change without notice.

**DO NOT SCALE THIS DRAWING**

**DIXON U.S.A.**

THE RIGHT CONNECTION™

TITLE: 3" DIXON™/BOSS-LOCK™ ADAPTER x 150# ANSI FLANGE CAM AND GROOVE FITTING

MATERIAL: CF8M STAINLESS STEEL

PART NUMBER: **300-AL-SSANSI**