	(18 29/32" [480mm])		(11 3/4 [298mr				
(10 3/4" [273mm]) (11 3/4" (298mm]) (4 48" ±1" (1219mm]	CROPH		78" ±1" 981mm] 6		7	
						48" ['] ±1" 1219mm]	
		8	4LAL-TFX45-43	4" SCHEDULE 40 PIPE	W/ TTMA FLANGE X		1
WIVEL SEALS (CONTACTING PRODUC				45 DEGREE	W/ TTMA FLANGE X	1219mm]	1
		7	440TFXTFAL11000	45 DEGREE 4" STYLE 40 O-RING FLAN	W/ TTMA FLANGE X CUT END SWIVEL W/ TTMA GES	1219mm]	1
WIVEL SEALS (CONTACTING PRODUC REASE: STANDARD (LITHIUM SEMI-S AX PRESSURE: 75 PSI STIMATED LOADING ARM WEIGHT: 34	YNTHETIC) 44.045 lbs	76	440TFXTFAL11000 4LAL-TFXTF-62	45 DEGREE 4" STYLE 40 O-RING FLAN 4" SCHEDULE 40 PIPE	W/ TTMA FLANGE X CUT END SWIVEL W/ TTMA GES W/ TTMA FLANGES	1219mm] ALUMINUM ALUMINUM ALUMINUM	1 1 1
WIVEL SEALS (CONTACTING PRODUC REASE: STANDARD (LITHIUM SEMI-S AX PRESSURE: 75 PSI	YNTHETIC) 44.045 lbs	7 6 5	440TFXTFAL11000 4LAL-TFXTF-62 ESB-CLAMP-4	45 DEGREE 4" STYLE 40 O-RING FLAN 4" SCHEDULE 40 PIPE 4" CL/	W/ TTMA FLANGE X E CUT END SWIVEL W/ TTMA GES W/ TTMA FLANGES AMP	1219mm]	1 1 1 1
WIVEL SEALS (CONTACTING PRODUC REASE: STANDARD (LITHIUM SEMI-S AX PRESSURE: 75 PSI STIMATED LOADING ARM WEIGHT: 34	YNTHETIC) 44.045 lbs	7 6 5 4	440TFXTFAL11000 4LAL-TFXTF-62 ESB-CLAMP-4 ESB1-A	45 DEGREE 4" STYLE 40 O-RING FLAN 4" SCHEDULE 40 PIPE 4" CL/ COUNTERE 4" STYLE 70 SPLIT FLAN	W/ TTMA FLANGE X CUT END SWIVEL W/ TTMA GES W/ TTMA FLANGES AMP BALANCE IGE SWIVEL W/ TTMA	1219mm] ALUMINUM ALUMINUM ALUMINUM IRON -	1 1 1 1 1 1 1
WIVEL SEALS (CONTACTING PRODUC REASE: STANDARD (LITHIUM SEMI-S AX PRESSURE: 75 PSI STIMATED LOADING ARM WEIGHT: 34 EMPERATURE RANGE: 0°F THRU 400	YNTHETIC) 44.045 lbs °F DATE:	7 6 5 4 3	440TFXTFAL11000 4LAL-TFXTF-62 ESB-CLAMP-4 ESB1-A SF470FGTFCS10CD	45 DEGREE 4" STYLE 40 O-RING FLAN 4" SCHEDULE 40 PIPE 4" CL/ COUNTERE 4" STYLE 70 SPLIT FLAN X 150 lbs. FLANG	W/ TTMA FLANGE X CUT END SWIVEL W/ TTMA GES W/ TTMA FLANGES AMP BALANCE IGE SWIVEL W/ TTMA ES & CB MOUNT	1219mm] ALUMINUM ALUMINUM ALUMINUM IRON - CARBON STEEL	1 1 1 1 1 1 1 1
WIVEL SEALS (CONTACTING PRODUC REASE: STANDARD (LITHIUM SEMI-S AX PRESSURE: 75 PSI STIMATED LOADING ARM WEIGHT: 34 EMPERATURE RANGE: 0°F THRU 400	YNTHETIC) 14.045 lbs °F	7 6 5 4	440TFXTFAL11000 4LAL-TFXTF-62 ESB-CLAMP-4 ESB1-A SF470FGTFCS10CD 4LCS-FGXFG-34	45 DEGREE 4" STYLE 40 O-RING FLAN 4" SCHEDULE 40 PIPE 4" CL/ COUNTERE 4" STYLE 70 SPLIT FLAN X 150 Ibs. FLANGI 4" SCHEDULE 40 PIPE N	W/ TTMA FLANGE X CUT END SWIVEL W/ TTMA GES W/ TTMA FLANGES AMP BALANCE IGE SWIVEL W/ TTMA ES & CB MOUNT W/ 150 LBS. FLANGES	1219mm] ALUMINUM ALUMINUM ALUMINUM IRON - CARBON STEEL CARBON STEEL	1 1 1 1 1 1 1 1 1 1
WIVEL SEALS (CONTACTING PRODUC REASE: STANDARD (LITHIUM SEMI-S AX PRESSURE: 75 PSI STIMATED LOADING ARM WEIGHT: 34 EMPERATURE RANGE: 0°F THRU 400 ISTRIBUTOR APPROVAL:	YNTHETIC) 44.045 lbs °F DATE: DATE:	7 6 5 4 3 2 1	440TFXTFAL11000 4LAL-TFXTF-62 ESB-CLAMP-4 ESB1-A SF470FGTFCS10CD 4LCS-FGXFG-34 SF430FGXFGCS108	45 DEGREE 4" STYLE 40 O-RING FLAN 4" SCHEDULE 40 PIPE 4" SCHEDULE 40 PIPE 4" STYLE 70 SPLIT FLAN X 150 lbs. FLANGE 4" SCHEDULE 40 PIPE V 4" STYLE 30 SPLIT FLAN Ibs. FLANGES & S	W/ TIMA FLANGE X CUT END SWIVEL W/ TIMA GES W/ TIMA FLANGES AMP BALANCE IGE SWIVEL W/ TIMA ES & CB MOUNT W/ 150 LBS. FLANGES NGE SWIVEL W/ 150 SCH. 80 ELBOW	1219mm] ALUMINUM ALUMINUM ALUMINUM IRON - CARBON STEEL CARBON STEEL CARBON STEEL CARBON STEEL	1 1 1 1 1 1 1 1 1 1 1 1
WIVEL SEALS (CONTACTING PRODUC REASE: STANDARD (LITHIUM SEMI-S AX PRESSURE: 75 PSI STIMATED LOADING ARM WEIGHT: 34 EMPERATURE RANGE: 0°F THRU 400 ISTRIBUTOR APPROVAL:	YNTHETIC) 44.045 lbs °F DATE:	7 6 5 4 3 2 1 1 ITEM NO.	440TFXTFAL11000 4LAL-TFXTF-62 ESB-CLAMP-4 ESB1-A SF470FGTFCS10CD 4LCS-FGXFG-34 SF430FGXFGCS108 PART NUMBER	45 DEGREE 4" STYLE 40 O-RING FLAN 4" SCHEDULE 40 PIPE 4" SCHEDULE 40 PIPE 4" STYLE 70 SPLIT FLAN X 150 Ibs. FLANG 4" SCHEDULE 40 PIPE V 4" STYLE 30 SPLIT FLAN Ibs. FLANGES & S DESCRI	W/ TTMA FLANGE X CUT END SWIVEL W/ TTMA GES W/ TTMA FLANGES AMP BALANCE IGE SWIVEL W/ TTMA ES & CB MOUNT W/ 150 LBS. FLANGES NGE SWIVEL W/ 150 SCH. 80 ELBOW PTION	1219mm] ALUMINUM ALUMINUM ALUMINUM IRON - CARBON STEEL CARBON STEEL CARBON STEEL CARBON STEEL CARBON STEEL CARBON STEEL	1 1 1 1 1 1 1 1 1 1 2 1 2 0TY.
WIVEL SEALS (CONTACTING PRODUC REASE: STANDARD (LITHIUM SEMI-S AX PRESSURE: 75 PSI STIMATED LOADING ARM WEIGHT: 34 EMPERATURE RANGE: 0°F THRU 400 ISTRIBUTOR APPROVAL:	YNTHETIC) 44.045 lbs °F DATE: DATE: NOTE:	7 6 5 4 3 2 1 1 ITEM NO.	440TFXTFAL11000 4LAL-TFXTF-62 ESB-CLAMP-4 ESB1-A SF470FGTFCS10CD 4LCS-FGXFG-34 SF430FGXFGCS108	45 DEGREE 4" STYLE 40 O-RING FLAN 4" SCHEDULE 40 PIPE 4" SCHEDULE 40 PIPE 4" STYLE 70 SPLIT FLAN X 150 Ibs. FLANGE 4" SCHEDULE 40 PIPE V 4" SCHEDULE 40 PIPE V 4" STYLE 30 SPLIT FLAN Ibs. FLANGES & S DESCRI	W/ TTMA FLANGE X CUT END SWIVEL W/ TTMA GES W/ TTMA FLANGES AMP BALANCE IGE SWIVEL W/ TTMA ES & CB MOUNT W/ 150 LBS. FLANGES NGE SWIVEL W/ 150 SCH. 80 ELBOW PTION	1219mm] ALUMINUM ALUMINUM ALUMINUM IRON - CARBON STEEL CARBON STEEL CARBON STEEL CARBON STEEL	1 1 1 1 1 1 1 1 1 1 2 1 2 1 2 7 7.