

NOTES:

- 1) ALL NUTS AND BOLTS ARE STAINLESS STEEL AND NON-SPARKING
- 2) ALL ELASTOMERS/GASKETS ARE APPROVED FOR GASOLINE SERVICE
- 3) MAX PRESSURE RATING FOR ASSEMBLY IS 150 PSI.

8	MN6	3/8-16 NUT	STAINLESS STEEL	16
7	33622	3/8 LOCK WASHER	STAINLESS STEEL	16
6	110120346	3/8-16 x 1.5" LONG	STAINLESS STEEL	16
5	5204LSNGP	API ADAPTER w/ ½" NPT PORT AND ½" HEX PLUG	SEE BOM	1
4	HANDLE	HANDLE FOR TANK CAR ASSEMBLIES	ALUMINUM	1
3	TETF4AL	4" TTMA FLANGE EXTENSION	ALUMINUM	1
2	40322TF	4" TANK TRUCK FLANGE GASKET	-	2
1	ATCF40SP75	TANK CAR NUT x TTMA FLANGE w/ 3/4" NPT PORT AND 3/4" HEX PLUG	SEE BOM	1
ITEM NO.	PART NUMBER	DESCRIPTION	MATERIAL	QTY.



The Right Connection™

PROPRIETARY AND CONFIDENTIAL

This drawing is owned by Dixon Valve & Coupling Co. and shall be returned upon demand. It is loaned on condition that it shall not be copied or reproduced or submitted to others without the owners consent. In accepting it subject to this condition the recipient further agrees that this drawing or any design detail or concept disclosed herein shall not be used in any way detrimental to or in competition with the owner. If the recipent does not agree to the terms of this agreement they shall return this drawing immediately. The information contained in this drawing is subject to change without notice.

TITLE:

THE RIGHT CONNECTION $^{\mathsf{TM}}$

U.S.A.

4" TANK CAR ASSEMBLY

DIXON [

MATERIAL:

PART NUMBER:

SEE BOM

DO NOT SCALE THIS DRAWING

SH0497706