5300/5400 Seal Conversion Kit to 5500-Series API Coupler

UPGRADE YOUR 5300/5400 TO THE NEWEST SEAL TECHNOLOGY

Dixon Recommends FKM-GFLT

Modern fuel requires FKM-GFLT for gasoline or ethanol blended fuel service. We offer the 5500-series with FKM-GFLT seals standard.

FKM-GFLT is a fluoroelastomer designed to retain the high heat and superior chemical resistance of the GF high-performance seals while improving the low-temperature performance.

We stock two seal material options: FKM-GFLT and FKM-B for diesel applications. For additional seal material options, please contact Dixon.

New Technology

- New seal profile increases burst pressure to 450 PSI and working pressure to 150 PSI
- Large offering of seal materials to serve a broader range of applications
- Once converted, the nose seal is easily replaced without disassembly
 of coupler or removal from loading arm

Features

· Kit contains: poppet, seal cylinder, and seals for nose assembly

Specifications

- Minimum temperature rating:
 - FKM-GFLT: -30°F (-34°C)
 - FKM-B: -10°F (-23°C)
- Maximum temperature rating:
 - FKM-GFLT: 400°F (204°C)
 - FKM-B: 400°F (204°C)
- Working pressure: 150 PSI
- Surge pressure: 350 PSI
- Tested without seal ejection: 450 PSI



5354K33

Dixon Bayco

7280 Union Centre Blvd West Chester, Ohio 45014 ph: 513.874.8499 fx: 513.874.8399 **dixonvalve.com**



Repair Parts

Descriptions	Part #
5300/5400 to 5500 nose seal conversion kit FKM-GFLT	5354K33
FKM-GFLT replacement nose seal kit for 5500G	5500RK11
FKM-GFLT complete seal repair kit for 5500G	5500RK5
5300/5400 to 5500 nose seal conversion kit FKM-B	5354K34
FKM-B replacement nose seal kit for 5500B	5500RK7
FKM-B complete seal repair kit for 5500B	5500RK1

© 2020 DVCC •5500CK_520