Dixon[®] Fire Submittal Sheet Brass Hex Adapters





DMH2525F

Dixon Brass Hex Adapters

Specifications

- □ Cast and/or forged brass; reducers
- Cast and/or forged brass; increasers
- Cast and/or forged brass; same size
- NOTE: All adapters rated for **175 PSI** standard working pressure and include washers if needed.

Layout

- Rigid Male x Male
- Rigid Female x Male
- Rigid Female x Female

NOTE: When ordering, the layout will follow (side 1 x side 2)

Nominal Size Thread Nominal Size Thread 3/4" NST 3/4" NST 1″ NPSH 1″ NPSH 1-1/2" NPT 1-1/2" NPT 2″ GHT 2″ GHT NYC (New York Corp) 2-1/2" 2-1/2" NYC (New York Corp) 3" 3" NYFD NYFD 3-1/2" QST (Quebec Standard) QST (Quebec Standard) 3-1/2" 4" CSA (Canadian Standard) 4″ CSA (Canadian Standard) WCT (Western Canada) 4-1/2" WCT (Western Canada) 4-1/2" 5″ NS1 (Nova Scotia) 5″ NS1 (Nova Scotia) 6" BCT (British Columbia) 6″ BCT (British Columbia) Other_____ Other

NOTE: Other local threads are available and are made to order. Ask Dixon Fire customer service for availability and lead times on combinations.

Replacement gaskets/washers are available upon request.

Dixon Fire

325 Arbor Ct Winchester, VA 22602 ph: 877.712.6179 fx: 800.283.4966 dixonvalve.com

© 2023 DVCC • BAFDC_723

Side 1 Size & Thread Options

Side 2 Size & Thread Options