

Dry Evotek Couplings

High-quality Material Selection

Applications

- Specifically designed for use in the chemical industry
- Rotating the coupling 120° clockwise opens the valves where the high pressure engagement between hose and tank unit ensures a strong connection

Sizes

- DN25, DN32, DN40, DN50, and DN80
- Additional sizes upon request

Features

- · Low connecting forces even against pressure
- Ergonomic handle (DN40 and bigger)
- · Good transmission ratio in the cam curve
- Wide range of chemical resistance due to high-quality material selection
- Minimized spillage during de-coupling

Materials

- · Body: stainless steel 1.4404
- Handle: PE (DN40 and bigger)
- O-rings: FPM, NBR, EPDM, FFKM
- · Thread seal: PTFE, FDA, and others upon request

Specification

 Working pressure 360 PSI at ambient temperature 70°F (21°C)

Approvals

- PED 2014/68/EU 4.3
- ATEX 2014/34/EU Category 3G

Adapters and couplers shown on reverse.



Dixon

1 Dixon Square Chestertown, MD 21620 ph: 877.963.4966 fx: 800.283.4966 dixonvalve.com





Female NPT	Body Size	Adapter x Female NPT Part #
1"	59.5 mm	DDEA100SS
1-1/2"	89 mm	DDEA150SS
2"	106 mm	DDEA200SS

Body Size

59.5 mm

89 mm

106 mm

150# Flange

1"

1-1/2"

2"

A	



Female NPT	Body Size	Coupler x Female NPT Part #
1"	59.5 mm	DDEC100SS
1-1/2"	89 mm	DDEC150SS
2"	106 mm	DDEC200SS

150# Flange	Body Size	Coupler x 150# Flange Part #
1"	59.5 mm	DDEC100SSFL
1-1/2"	89 mm	DDEC150SSFL
2"	106 mm	DDEC200SSFL



© 2023 DVCC • EVOTEK_923



Adapter x 150# Flange

Part #

DDEA100SSFL

DDEA150SSFL

DDEA200SSFL