The Right Connection®

Specifications:

Single Clapper (Rear Outlet/Straight)

 Cast Brass Fire Department Connection; dual female inlets x female NPT thread outlet; 250 PSI

Single Clapper (Bottom Outlet/90°)

 Cast Brass Fire Department Connection; dual female inlets x female NPT thread outlet; 250 PSI

Double Clapper (Rear Outlet/Straight)

 Cast Brass Fire Department Connection; dual female inlets x female NPT thread outlet; 175 PSI

Product Options:

Nominal Size and Layout:

Single Clapper (Rear Outlet) 4" x (2) 2-1/2" Double Clapper (Rear Outlet) 4" x (2) 2-1/2"

- 🔲 4" x (2) 3"
- G" x (2) 2-1/2"
- G" x (2) 3"

Triple Clapper (Rear Outlet)

- 4" x (3) 2-1/2"
- G" x (3) 2-1/2"

Single Clapper (Bottom Outlet)

4" x (2) 2-1/2"

Double Clapper (Bottom Outlet)

- 4" x (2) 2-1/2"
- 4" x (2) 3"
- G" x (2) 2-1/2"
- G" x (2) 3"

Triple Clapper (Bottom Outlet)

- 4" x (3) 2-1/2"
- G" x (3) 2-1/2"

Approvals Needed:

- 🔲 UL
- ULC
- 🔲 FM
- None

Double Clapper (Bottom Outlet/90°)

• Cast Brass Fire Department Connection; dual female inlets x female NPT thread outlet; **175 PSI**

Triple Clapper (Rear Outlet/Straight)

 Cast Brass Fire Department Connection; triple female inlets x female NPT thread outlet; **175 PSI**

Triple Clapper (Bottom Outlet/90°)

• Cast Brass Fire Department Connection; triple female inlets x female NPT thread outlet; **175 PSI**

Inlet Threads:

|--|--|

- NYFD
- 🔲 NYC
- NPSH
- CSA
- Other _____

Finish:

- Raw cast
- Polished
- Polished chrome
- Rough chrome (Chromed raw cast)
- Other____

Optional Caps / Plugs:

- Pin lug with chain
- Rocker lug with chain

Labeling:

- Standpipe
- Auto sprinkler
- Standpipe/Auto sprinkler
- None



Model Dimensions



SCS4025F



DCS4025F-C



TCS4025F-SP









90SCS4025F



90DCS4025F-P



90TCS4025F-NB







Warning: Dimensions are for reference only, consult Dixon® for dimensions of other available configurations

Dixon Fire

325 Arbor Ct Winchester, VA 22602 ph: 877.712.6179 fx: 800.283.4966 dixonvalve.com

© 2023 DVCC • EFDC_423