





carbon steel

**Only use the crimp style shanks with the crimp style sleeves and ferrules.** Due to differences in dimensions and tolerances for safety reasons, do not interchange other manufacturers' products with Dixon® products.



stainless steel

Hose I.D.	Hose O.D.		Working Pressure (PSI)	Ferrule I.D.	Ferrule Wall Thickness	Ferrule Overall Length	Carbon Steel Part #	304 Stainless Steel Part #
	From	To						
4"	4-13/64"	4-16/64"	400	4.313"	.090"	4"	CF400-1CS	CF400-1SS
	4-17/64"	4-20/64"		4.375"	.090"	4"	CF400-2CS	CF400-2SS
	4-21/64"	4-24/64"		4.438"	.090"	4"	CF400-3CS	CF400-3SS
	4-25/64"	4-28/64"		4.500"	.090"	4"	CF400-4CS	CF400-4SS
	4-29/64"	4-32/64"		4.563"	.090"	4"	CF400-5CS	CF400-5SS
	4-33/64"	4-36/64"		4.625"	.090"	4"	CF400-6CS	CF400-6SS
	4-37/64"	4-40/64"		4.688"	.090"	4"	CF400-7CS	CF400-7SS
	4-41/64"	4-44/64"		4.750"	.090"	4"	CF400-8CS	CF400-8SS
	4-45/64"	4-48/64"		4.813"	.090"	4"	CF400-9CS	CF400-9SS
	4-49/64"	4-52/64"		4.875"	.090"	4"	CF400-10CS	CF400-10SS
	4-53/64"	4-56/64"		4.938"	.090"	4"	CF400-11CS	CF400-11SS
	4-57/64"	4-60/64"		5.000"	.090"	4"	CF400-12CS	CF400-12SS
	4-61/64"	5"		5.063"	.090"	4"	CF400-13CS	CF400-13SS
	5-1/64"	5-4/64"		5.125"	.090"	4"	CF400-14CS	CF400-14SS
	5-5/64"	5-8/64"		5.188"	.090"	4"	CF400-15CS	CF400-15SS
	5-9/64"	5-12/64"		5.250"	.090"	4"	CF400-16CS	CF400-16SS

**Only use the crimp style shanks with the crimp style sleeves and ferrules.** Due to differences in dimensions and tolerances for safety reasons, do not interchange other manufacturers' products with Dixon® products.



heavy duty

- **400 PSI** working pressure with a minimum 4:1 safety factor (hose burst: hose working pressure) is only achieved with heavy duty (HD) crimp ferrules, CF400-6CSDH through CF400-16CSDH

Hose I.D.	Hose O.D.		Ferrule Wall Thickness	Ferrule I.D.	Ferrule Overall Length	Carbon Steel Part #
	From	To				
4"	4-33/64"	4-36/64"	0.120"	4.625"	4"	CF400-6CSHD
	4-37/64"	4-40/64"	0.120"	4.688"	4"	CF400-7CSHD
	4-41/64"	4-44/64"	0.120"	4.750"	4"	CF400-8CSHD
	4-45/64"	4-48/64"	0.120"	4.813"	4"	CF400-9CSHD
	4-49/64"	4-52/64"	0.120"	4.875"	4"	CF400-10CSHD
	4-53/64"	4-56/64"	0.120"	4.938"	4"	CF400-11CSHD
	4-57/64"	4-60/64"	0.120"	5.000"	4"	CF400-12CSHD
	4-61/64"	5"	0.120"	5.063"	4"	CF400-13CSHD
	5-1/64"	5-4/64"	0.120"	5.125"	4"	CF400-14CSHD
	5-5/64"	5-8/64"	0.120"	5.188"	4"	CF400-15CSHD
	5-9/64"	5-12/64"	0.120"	5.250"	4"	CF400-16CSHD