

HSG-Series Hygienic Sight Glass



Applications

- Used widely in the food, dairy, and beverage sanitary processes to view products and fluids
- Can be used in industrial applications when you want to CIP and require 316L stainless steel construction

Sizes

- 1/2" to 6"
 - single pin clamp: 1" to 6"; EPDM or FKM gasket - bolted clamp: 1/2" to 6"; PTFE gasket

Features

- 3A CIP certified
- · Higher pressure range than other sight glasses
- · Easy assembly and disassembly
- Rubber seals are I-line gaskets
- Clamp protects glass from getting damaged
- Patent pending assembly design

Materials

- Body: 316L stainless steel
- · Sight glass: polycarbonate
- Gaskets: PTFE, EPDM, or FKM



Single Pin Clamp



Bolted Clamp

Dixon Sanitary

N25 W23040 Paul Road Pewaukee, WI 53072 ph: 800.789.1718 fx: 800.789.4046 dixonvalve.com





Series	Elastomer 1	Size	Body One Connection	Body Two Connection	Surface Finish
HSG	E = EPDM V = FKM P = PTFE	050 = 1/2" ²	B = weld	C = triclamp B = weld	A = ≤32 Ra (ID mechanical polish) B = ≤25 Ra (ID mechanical polish) C = ≤20 Ra (ID mechanical polish) D = ≤15 Ra (ID electropolish) E = ≤10 Ra (ID electropolish)
		075 = 3/4" ²			
		100 = 1"			
		150 = 1-1/2"			
		200 = 2"			
		250 = 2-1/2"			
		300 = 3"			
		400 = 4"			
		600 = 6"			

Part Number Key

 1 EPDM or FKM with single pin clamp, PTFE with bolted clamp 2 1/2" and 3/4" available only with PTFE elastomers

Pressure Ratings

Size	PSI @ 70°F (21°C)	PSI @ 200°F (93°C)
1/2" - 1"	500	300
1-1/2"	450	250
2"	400	200
2-1/2"	350	175
3"	250	125
4"	80	40
6"	50	25

NOTE: Repair kits consisting of two gaskets are available for all sizes and configurations.

© 2021 DVCC • HSG_1221