Modular Connection System (MCS)

Applications

 Agricultural, automotive, demolition, die casting, mobile construction equipment, oil & gas, railroad, snow & ice removal, steel, forestry, and mining

Sizes

• 3/8", 1/2", 3/4", and 1"

Features

- · A single system that holds multiple hydraulic quick couplings
- · Modularity: Blocks can be configured to meet customer needs (patent pending)
- Innovative coupling retention system for easy field repair (patent pending)
- Versatile: Up to 10 couplings can be used at once depending on size
- 450+ configurations possible
- 17-4 stainless steel alignment pins maximize corrosion resistance
- · Cam-style latching mechanism helps provide a smooth connection
- HTE (male) and HTZ (female) coupling technology enables connections under residual pressure

Approvals

· All working configurations approved 3000 PSI working pressure



The Right Connection®

Dixon Quick Coupling

2925 Chief Court Dallas, NC 28034 ph: 800.839.8980 • 704.334.9175 fx: 800.839.9022 • 704.334.9002 dixonvalve.com

NOTE: Please see back page for part number key

MCM11110-A000

MCF11110-A000



Part Number Key

Modular Connection System Ex. MCF22010-B001		МС	Half Designator F-M	Number of 1" Fittings 0-4	Number of 3/4" Fittings 0-4	of 1/2"	Number of 3/8" Fittings 0-X	of 1/4"	Variant Category A-K	Variant Number 000-999
Half Designator	Code	-		0-4	0-4	0-7	0-7			000-999
Fixed	F									
Mobile	М									
Number of 1" Fittings	Code	-								
Zero to four	0-4									
Number of 3/4" Fittings	Code	-								
Zero to four	0-4									
Number of 1/2" Fittings	Code	-								
Zero to nine	0-9									
Ten	Х									
Number of 3/8" Fittings	Code	-								
Zero to nine	0-9									
Ten	Х									
Number of 1/4" Fittings	Code	-								
Zero to nine	0-9									
Ten	Х									
Variant Category	Code	-								
Default	А									
Fitting arrangement	В									
Custom thread ends	С									
Custom dust caps	D									
Electrical connections	E									
Custom seals	F									
Custom labeling	G									
Custom anodization	Н									
Multiple variations	J									
Custom brackets	К									
Variant Number	Code	-								
000 to 999	000-999									

NOTE: The MCS utilizes nitrile rubber seals and NPTF end connections unless otherwise specified. Certain configurations may require consultation. Contact Dixon for more information.

1/4" size option will be available in the future

© 2024 DVCC • MCS_0224