DATA SHEET OSHA-Compliant Products





Dixon® OSHA-compliant products will help you meet several OSHA requirements concerning the use of hose couplings and related accessories.

Please visit us at dixonvalve.com for complete product descriptions and more information on the rest of Dixon's product line. OSHA regulations may be viewed at osha.gov.

OSHA Standard	Dixon Product	Product Description
1926.302(b2)	Air King® safety clip	For securing Air King universal couplers
1910.169 1926.306	ASME air receiver manifolds	7-gallon tank with Air King couplers that have a safety check valve 7-gallon tank with Watts filter 7-gallon tank frame
1910.147	Wilkerson lockout valve	Used during maintenance and service procedures of pneumatically operated equipment Inline or surface mountable
1910.95	Conical muffler	Reduces noise levels below 90 dBA
1910.242(b) 1910.95	Extended nozzle pistol grip	Tip pressure will not exceed 30 PSI Reduces noise levels below 90 dBA
1910.242(b) 1910.95	Pistol grip safety blowgun; premium safety blowgun	Tip pressure will not exceed 30 PSI Reduces noise levels below 90 dBA
1910.242(b)	Push-button, controlled pressure safety blowgun	Tip pressure will not exceed 30 PSI
1910.242(b) 1910.95	Safety blowgun; safety air booster blowgun	Tip pressure will not exceed 30 PSI Reduces noise levels below 90 dBA
1926.302(b7)	Safety check valve	Prevents hose whip during accidental fitting separation or pressure surge
1926.302(b1)	King Cable® nylon safety restraints, and King Cable safety whipsock	Prevents hose whip during accidental separation of hose assembly

Dixon 1 Dixon Sq., Chestertown, MD 21620 ph: 877.963.4966 • fx: 800.283.4966 dixonvalve.com

© 2023 DVCC • OSHA_1223