

T-Series

10,000 PSI THREAD-TOGETHER QUICK DISCONNECT

Applications

 Hydraulic tools, jacks, hand pumps, fire rescue tools, crimping, bolting and power units

Industries

 Construction, oil and gas, fire and rescue, utilities, mining, and manufacturing

Market Buzz Words

· Porta power, jack hose, and high-torque

Interchange Data

- 10,000 PSI thread-together interchange ISO 14540
- Interchangeable with Parker 3000-Series, Enerpac C604, Stucchi IVHP, Hansen WS56000, DNP PVM

Sizes

• Body: 1/4" and 3/8"

Features

- Chrome steel ball valve is mechanically seated to improve pressure sealing performance
- · Replacement O-ring and back up ring kit available

Material

- Nitrile O-ring with TPC-ET back-up ring
- · Available in steel and 316 stainless steel
- Steel componentry is plated using RoHS-compliant trivalent chrome enhances corrosion resistance

Specifications

- Maximum working pressure: 10,000 PSI
- · Ball valve and poppet valve options
- NPTF male and female threads available

Dixon Quick Coupling

2925 Chief Court Dallas, NC 28034 ph: 800.839.8980 • 704.334.9175 fx: 800.839.9022 • 704.334.9002 **dixonvalve.com**

© 2021 DVCC • TSERIES_121