# Vent-Lock<sup>®</sup> Safety Cam & Groove Couplings

#### Application

• Transfer of fluids and solids, with a safer disconnection

#### Features

- Safety release cam & groove couplings permit the release of static pressure when disconnecting hose assemblies
- Venting system protects operator from being sprayed with hazardous or nonhazardous fluids or solids
- Does not interchange with standard cam & groove products; use only with Dixon L-style fittings
- Safety orange cam arms
- · Consult Dixon for availability of other materials

#### Specifications

- Rated to 250 PSI; recommendation based on the use of mating Dixon<sup>®</sup> L-style fittings at ambient temperature 70°F (21°C) with standard nitrile rubber seal installed. For use at elevated temperatures or other unusual operating conditions, consult Dixon
  - 1", 1-1/2" and 2" sizes have a maximum working pressure of **250 PSI**
  - 3" maximum working pressure **150 PSI** with King Crimp<sup>®</sup> ferrules, crimp sleeves, and bands at **125 PSI**
  - 4" maximum working pressure **150 PSI** with King Crimp ferrules, crimp sleeves, and bands at **100 PSI**

#### **Attachment Options**

• Ferrules, sleeves, bands, and other reliable options

#### Type A Adapters Adapter x Female NPT

Size	316 Stainless Steel Part #	Aluminum Part #
1"	L100-A-SS	
1-1/2"	L150-A-SS	
2"	L200-A-SS	
3"	L300-A-SS	
4"		L400-A-AL

# Type C Couplers

#### **Coupler x Hose Shank**

Size	316 Stainless Steel Part #
1"	L100-C-SS
1-1/2"	L150-C-SS
2"	L200-C-SS

## EZ Boss-Lock Type C Couplers Coupler x Hose Shank

Size	316 Stainless Steel Part #	Aluminum Part #
1"	RLC100EZ	
1-1/2"	RLC150EZ	
2"	RLC200EZ <sup>1</sup>	
3"	RLC300EZ1	
4"		ALC400EZ <sup>1</sup>

<sup>1</sup> Has drop shank



The Right Connection®



#### Adapter x Female NPT



Coupler x Hose Shank



Coupler x Hose Shank

# **Dixon Specialty Products**

225 Talbot Blvd. Chestertown, MD 21620 ph: 888.226.4673 fx: 410.778.1958 **dixonvalve.com** 

# Vent-Lock® Safety Cam & Groove Couplings

















I	
Size	316 Stainless Steel Part #
]"	RLD100EZ
1-1/2"	RLD150EZ
2"	RLD200EZ
3"	RLD300EZ

## Type E Adapters Adapter x Hose Shank

Size	316 Stainless Steel Part #	
1"	L100-E-SS	
1-1/2"	L150-E-SS	
2"	L200-E-SS	
3"	L300-E-SS	

# **Type DC Dust Caps**

Size	316 Stainless Steel Part #
1"	L100-DC-SS
1-1/2"	L150-DC-SS
2"	L200-DC-SS

# **Type DP Dust Plugs**

Size	316 Stainless Steel Part #
1"	L100-DP-SS
1-1/2"	L150-DP-SS
2"	L200-DP-SS
3"	L300-DP-SS

# EZ Boss-Lock Type H Dust Caps

Size	316 Stainless Steel Part #	Aluminum Part #
1"	RLH100EZ	
1-1/2"	RLH150EZ	
2"	RLH200EZ	
3"	RLH300EZ	
3"		ALH400EZ

# Dixon<sup>®</sup> Handle Assembly

FeaturesUse only with Dixon Vent-Lock couplers

- Includes handle, ring, and pin
  - menades nanale, mig, and pin

Size	316 Stainless Steel Part #	
1"	L100-HSCRP-SI	
1-1/2" - 2"	L200-HSCRP-SI	

## EZ Boss-Lock Handle Assembly

- FeaturesUse only with EZ Boss-Lock Vent-Lock couplers
- Includes handle, ring, and pin

Size	316 Stainless Steel Part #
1"	LRHEZ175
1-1/2" - 2"	LRHEZ152
3"	LRHEZ34

© 2022 DVCC • VLCGC\_422