# Data Sheet Dixon<sup>®</sup> Colored Double Jacket Fire Hose



# 800# Colored Double Jacket Fire Hose

### Applications

- Industrial washdown
- Water discharge/transfer
- Municipal firefighting
- Standpipe/auto sprinkler supply line
- Master stream nozzle supply
- · High pressure water transfer

#### Features

- Double jacket lined hose
- Optional colors: black, blue, green, orange, purple, red, tan, and yellow
- Other threads and configurations are available upon request, contact Dixon
- Uncoupled availability upon request
- Made in the USA

# **Specifications:**

- Temperature range: -60°F to 112°F (-51°C to 44°C)
- Burst pressure: 1200 PSI at ambient temperature 70°F (21°C)
- Service test pressure: 800 PSI at ambient temperature 70°F (21°C)
- Working pressure: 400 PSI at ambient temperature 70°F (21°C)



# Materials:

- All polyester outer jacket
- Thermoplastic polyurethane liner
- EPDM available upon special request
- NOTE: Meets the following standards: NFPA 1960, UL-19, MIL-H-24606, and MIL A-A-59226

# **Coupled with Female and Male Expansion Couplings**

Size	Length	Color	Rocker Lug Aluminum NST (NH) Part #	Rocker Lug Aluminum NPSH Part #
1-1/2″	50'	yellow	D815Y50RAF	D815Y50RAS
	100'		D815Y100RAF	D815Y100RAS
	50'	red	D815R50RAF	D815R50RAS
	100'		D815R100RAF	D815R100RAS
	50'	orange	D815OR50RAF	D815OR50RAS
	100'		D8150R100RAF	D8150R100RAS
2-1/2"	50'	yellow	D825Y50RAF	D825Y50RAS
	100'		D825Y100RAF	D825Y100RAS
	50'	red	D825R50RAF	D825R50RAS
	100'		D825R100RAF	D825R100RAS
	50'	orange	D825OR50RAF	D8250R50RAS
	100'		D8250R100RAF	D8250R100RAS

NOTE: 1-3/4", 2", 3", 4", and 5" sizes are available upon request

**Dixon** 1 Dixon Sq., Chestertown, MD 21620 ph: 877.963.4966 • fx: 800.283.4966 **dixonvalve.com** 

COLOREDDJFH\_625