



## 500# Colored Single Jacket Fire Hose

## Applications

- Industrial washdown
- Water discharge/transfer
- Standby fire hose

## Features

- Single jacket lined hose
- Lightweight, easy to store
- Optional colors: black, blue, green, orange, purple, red, tan, and yellow
- Other threads and configurations are available upon request, contact Dixon
- Made in the USA
- Uncoupled availability upon request

### Materials:

- All polyester outer jacket
- Thermoplastic polyurethane liner
- EPDM available upon special request

### Specifications:

- Temperature range: **-30°F to 112°F (-34°C to 44°C)**
- Burst pressure: **750 PSI** at ambient temperature **70°F (21°C)**
- Service test pressure: **500 PSI** at ambient temperature **70°F (21°C)**
- Working pressure: **250 PSI** at ambient temperature **70°F (21°C)**

NOTE: Meets the following standards: NFPA 1960 and UL-19

### Coupled with Standard Female and Male Expansion Couplings

Size	Length	Color	Rocker Lug Aluminum NST (NH) Part #	Rocker Lug Aluminum NPSH Part #
1-1/2"	50'	yellow	A515Y50RAF	A515Y50RAS
		red	A515R50RAF	A515R50RAS
		orange	A515OR50RAF	A515OR50RAS
2-1/2"		yellow	A525Y50RAF	A525Y50RAS
		red	A525R50RAF	A525R50RAS
		orange	A525OR50RAF	A525OR50RAS

## Dixon

1 Dixon Sq., Chestertown, MD 21620

ph: 877.963.4966 • fx: 800.283.4966

**dixonvalve.com**

© 2025 DVCC

COLOREDSJFH\_625