

Pneumatically Actuated 3-Way Stainless Steel Ball Valves - 'T / L' Port

Sanitary
Fittings



Features:

3-Way Stainless Steel Ball Valve

- full port ball valves with FNPT ends
- body and ball: CF8M stainless steel
- seats and seals: RTFE
- blow-out proof stem
- live-loaded stem packing
- ISO 5211 mounting pad
- working pressure: ¼" to 1": **1000 PSI WOG**; 1¼" to 2": **800 PSI WSP**
- maximum temperature: **350°F (177°C)**

Rack and Pinion Actuator

- body: hard anodized aluminum
 - anti-blowout pinion: nickel plated
 - O-rings: Buna-N
 - NAMUR mounting
 - bi-directional stops for ±5° travel adjustment
 - 80 PSI plant air required
 - visual position indication
 - maximum operating pressure: **120 PSI**
 - temperature range: **-40°F to 200°F (-40° to 93°C)**
 - tested to one million cycles
 - for spring return actuators must note fail position
- A flow path needs to be selected at time of order. See page 651 for flow path options.
 - Customer verification is critical. If flow path needs to be changed after being shipped, labor and shipping charges will apply.

A wide variety of options are available: spring return (normally closed) and double acting actuators, switches, solenoids, positioners, etc. Contact Dixon Sanitary at 800.789.1718.

Even though there are torque safety factors built into our automated ball valve packages, actual service conditions must also be considered when selecting the proper product for the appropriate application.

For example: Severe service conditions such as dirty water, dirty air, all slurries, raw sewage water, oils, and other viscous fluids can have a dramatic affect in raising the torque requirements of ball valves as much as 75% and therefore larger actuators may be required. Please consult Dixon® when dealing with these types of applications.

