

## Notched Turned Back Nipples

**Features:**

- When used with an appropriate notched ferrule, these fittings can be swaged or crimped onto hose providing improved shank retention.
- When used with double bolt or band clamps, notched turn back nipples provide shank retention similar to that of the King™ turned back nipples.
- The stem can be removed from a damaged hose by cutting away the ferrule without necessarily damaging the fitting.
- For use with lap joint flanges on page 688.



## Special pushers required:

1½" stem - RN150NOPUSH

2" stem - RN200NOPUSH

2½" stem - RN250NOPUSH

3" stem - RN300NOPUSH

4" stem - RN400NOPUSH

Size	Carbon Steel Part #	316 Stainless Steel Part #
1½"	<b>N150NO</b>	<b>RN150NO</b>
2"	<b>N200NO</b>	<b>RN200NO</b>
2½"	<b>N250NO</b>	<b>RN250NO</b>
3"	<b>N300NO</b>	<b>RN300NO</b>
4"	<b>N400NO</b>	<b>RN400NO</b>

- For additional information on pipe dimensions please reference [dixonvalve.com](http://dixonvalve.com).

## Notched Ferrules

- reference notched shanks above and adapters on page 143
- Dixon® stems and ferrules are specifically designed to be used together as a coupling system. Due to differences in dimensions and tolerances for safety reasons, do not use other manufacturer's stems or ferrules with Holedall™ products.



Size	Hose OD		304 Stainless Steel Part #
	From	To	
1½"	1-60/64"	2-12/64"	<b>GAS2334NO</b>
	2-4/64"	2-22/64"	<b>GAS2370NO</b>
2"	2-30/64"	2-44/64"	<b>GAS2709NO</b>
	2-42/64"	2-54/64"	<b>GAS2885NO</b>
2½"	2-54/64"	3"	<b>GAS3012NO</b>
	3-1/64"	3-13/64"	<b>GAS3260NO</b>
3"	3-30/64"	3-46/64"	<b>GAS3760NO</b>
	3-47/64"	3-54/64"	<b>GAS3885NO</b>
4"	4-40/64"	4-47/64"	<b>GAS5010NO</b>