

## Type B

## Male with Machined Hose Shank

## Features:

- Dixon® combination nipple style hose shank machined from Schedule 40 pipe
- recommended for use with steel King Crimp™ sleeves



Size	Galvanized Steel Part #
2"	<b>MC3092ST25</b>
3"	<b>MC3093ST35</b>
4"	<b>MC3094ST40</b>
6"	<b>MC3096ST60</b>
8"	<b>MC3098ST80</b>

## Male x 150# ASA Flange



Size	Galvanized Steel Part #
4"	<b>MC3134</b>
6"	<b>MC3136</b>
8"	<b>MC3138</b>
10"	<b>MC31310<sup>1</sup></b>
12"	<b>MC31312<sup>1</sup></b>

<sup>1</sup> 10" and 12" supplied with ACB304 lever assist bar on page 261

- For flange dimensions, diagrams and additional information please reference [dixonvalve.com](http://dixonvalve.com).

## Male Weld-On



Size	Unplated Steel Part #
2"	<b>3032</b>
3"	<b>3033</b>
4"	<b>3034</b>
6"	<b>3036</b>
8"	<b>3038</b>
10"	<b>30310</b>
12"	<b>30312</b>

- female and male fittings are commonly used for butt-welding to pipe

## Heavy Duty Female x Dixon® Combination Nipple Hose Shank



Size	Galvanized Steel Part #
2"	<b>FC3102ST25</b>
3"	<b>FC3103ST35</b>
4"	<b>FC3104ST40</b>
6"	<b>FC3106ST60</b>
8"	<b>FC3108ST80</b>