

Sand Blast Couplings

Features:

- designed for use on sand blast hose
- supplied with screws
- nozzle holders have 1¼" NPSM thread
- pressure: 110 PSI at ambient temperature **70°F (21°C)**
- abrasive blasting equipment must have hose safety cables (page 362) or hose coupling safety locks installed to read safety clips



Installation:

- 1) Ends of hose must be cut square to fit snug against metal end.
- 2) Holding hose tight to end of fitting, insert screws and turn in full, putting screw 180° from first to ensure best centering.
- 3) After all screws have been placed, check tube opposite screws to be sure screws have not penetrated completely through.
- 4) On quick couplings, insert safety clips

Hose Ends



Hose Size	Hose OD	Brass Part #	Aluminum Part #
¾"	1-1/2"	<b>BSB75</b>	<b>ASB75</b>
1"	1-7/8"	<b>BSB100</b>	<b>ASB100</b>
1¼"	2-5/32"	<b>BSB125</b>	<b>ASB125</b>
1½"	2-3/8"	<b>BSB150</b>	<b>ASB150</b>

Nozzle Holders



Hose Size	Hose OD	Brass Part #	Aluminum Part #
¾"	1-1/2"	<b>BNH75</b>	<b>ANH75</b>
1"	1-7/8"	<b>BNH100</b>	<b>ANH100</b>
1¼"	2-5/32"	<b>BNH125</b>	<b>ANH125</b>
1½"	2-3/8"	<b>BNH150</b>	<b>ANH150</b>

Female Threaded Ends



Hose Size	Brass Part #	Aluminum Part #
1¼"	<b>BSC125</b>	<b>ASC125</b>
1½"	<b>BSC150</b>	<b>ASC150</b>

- does not include screws

Replacement Parts



black nitrile



urethane

Description	Part #
<i>black nitrile</i> replacement gasket	<b>SBG</b>
<i>urethane</i> replacement gasket	<b>USBG</b>
replacement screws for sand blast couplings (sold in package quantity of 8 only)	<b>SBCS</b>