

## Air Chief Automotive Interchange Couplings

**Features:**

- pressure rating: **300 PSI**
- temperature range: **-40°F to 250°F (-40°C to 121°C)**
- couplers are semi-automatic
- interchanges with popular makes of automotive quick-connect fittings such as Amflo, Dill, Milton and Truflate, some makes do not interchange with any others, if you plan to interchange these couplings make sure you have plug ends with the proper configuration

### Semi-Automatic

#### Female Threaded Couplers

Body Size	Female NPT	Flow Rating at 100 PSI	Brass Part #	Steel Part #
1/4"	1/8"	37 CFM	<b>DC221</b>	---
	1/4"	37 CFM	<b>DC2</b>	---
	3/8"	37 CFM	<b>DC223</b>	---
3/8"	1/4"	70 CFM	---	<b>DC8</b>
	3/8"	70 CFM	---	<b>DC6</b>
	1/2"	70 CFM	---	<b>DC624</b>



#### Male Threaded Couplers

Body Size	Male NPT	Flow Rating at 100 PSI	Brass Part #	Steel Part #
1/4"	1/8"	37 CFM	<b>DC101</b>	---
	1/4"	37 CFM	<b>DC1</b>	---
	3/8"	37 CFM	<b>DC103</b>	---
3/8"	1/4"	70 CFM	---	<b>DC7</b>
	3/8"	70 CFM	---	<b>DC5</b>
	1/2"	70 CFM	---	<b>DC504</b>



#### Standard Hose Barb Couplers

Body Size	Hose ID	Flow Rating at 100 PSI	Brass Part #	Steel Part #
1/4"	1/4"	37 CFM	<b>DC242</b>	---
	3/8"	37 CFM	<b>DC244</b>	---
3/8"	3/8"	70 CFM	---	<b>DC644</b>
	1/2"	70 CFM	---	<b>DC645</b>



#### Push-On Hose Barb Couplers

Body Size	Hose ID	Flow Rating at 100 PSI	Brass Part #	Steel Part #
1/4"	1/4"	37 CFM	<b>DC242L</b>	---
	3/8"	37 CFM	<b>DC244L</b>	---
3/8"	3/8"	70 CFM	---	<b>DC644L</b>



### Air Chief Automotive Actual Size Profile Charts

