

Air Chief ARO Speed Interchange Couplings

- pressure rating: 300 PSI at ambient temperature 70°F (21°C)
- interchanges with ARO 210 and 310 designs
- couplers shut-off when disconnected

Female Threaded Plugs



| Body Size | Female NPT | Flow Rating at 100 PSI | Steel Part # |
|--------------|------------|---------------------------|-----------------|
| 1/4" | 1/4" | 37 CFM | DCP38 |
| | 3/8" | 37 CFM | DCP3823 |
| 3/8" | 3/8" | 70 CFM | DCP36 |

Male ThreadedPlugs



| Body | Male NPT | Flow Rating | Steel |
|------|--------------|-------------|---------|
| Size | IVIAIE INF I | at 100 PSI | Part # |
| 1/4" | 1/4" | 37 CFM | DCP37 |
| | 3/8" | 37 CFM | DCP3703 |
| 3/8" | 3/8" | 70 CFM | DCP35 |

Standard Hose Barb



| Body | Hose ID | Flow Rating | Steel |
|------|---------|-------------|---------|
| Size | | at 100 PSI | Part # |
| 1/4" | 1/4" | 37 CFM | DCP3742 |

Push-On Hose Barb



| Body | Hose ID | Flow Rating | Steel |
|------|-----------|-------------|----------|
| Size | I lose iD | at 100 PSI | Part # |
| 1/4" | 1/4" | 37 CFM | DCP3742L |
| | 3/8" | 37 CFM | DCP3744L |

Ball Swivel Plug

Features:







