

## D.O.T. Push-In Fittings

### Features:

- materials:
  - body (straights) tube, supports and grippers: brass CA360
  - forged elbows and tees: brass CA377
  - O-ring: Buna-N
- suitable for use up to the maximum working pressure of the plastic tubing used, also suitable for vacuum service
- temperature range: **-40°F to 212°F (-40°C to 100°C)**
- pre-applied thread sealant (Loctite 516®) on all male pipe threads
- compatible tubing: SAE J844
- meets D.O.T FMVSS 571.106 and SAE J1131, SAE J2494-1 and SAE J2494-3



### Male Connectors

| Tube OD | Male NPTF | Part #            | Pkg Qty |
|---------|-----------|-------------------|---------|
| 1/4"    | 1/8"      | <b>AQ68DOT4X2</b> | 10      |
| 1/4"    | 1/4"      | <b>AQ68DOT4X4</b> | 10      |
| 1/4"    | 3/8"      | <b>AQ68DOT4X6</b> | 5       |
| 3/8"    | 1/4"      | <b>AQ68DOT6X4</b> | 10      |
| 3/8"    | 3/8"      | <b>AQ68DOT6X6</b> | 10      |

### Union Connectors



| Tube OD | Part #          | Pkg Qty |
|---------|-----------------|---------|
| 1/4"    | <b>AQ62DOT4</b> | 10      |
| 3/8"    | <b>AQ62DOT6</b> | 10      |

### Male Elbows



| Tube OD | Male NPTF | Part #            | Pkg Qty |
|---------|-----------|-------------------|---------|
| 1/4"    | 1/8"      | <b>AQ69DOT4X2</b> | 10      |
| 1/4"    | 1/4"      | <b>AQ69DOT4X4</b> | 10      |
| 3/8"    | 1/4"      | <b>AQ69DOT6X4</b> | 10      |

### D.O.T. Push-In Male Swivel Elbows



| Tube OD | Male NPTF | Part #             | Pkg Qty |
|---------|-----------|--------------------|---------|
| 1/4"    | 1/8"      | <b>AQ69DOTS4X2</b> | 10      |
| 1/4"    | 1/4"      | <b>AQ69DOTS4X4</b> | 10      |
| 1/4"    | 3/8"      | <b>AQ69DOTS4X6</b> | 10      |
| 3/8"    | 1/4"      | <b>AQ69DOTS6X4</b> | 10      |
| 3/8"    | 3/8"      | <b>AQ69DOTS6X6</b> | 5       |