

## Dixon® Vapor Recovery

## Couplers

## Material:

- seal: Buna N and FKM

## Features:

- 'floating bridge' poppet design allows optimal flow
- machined hose shank ensures easier insertion into hose and better sealing
- durable, easy to couple stainless cam arms
- big wings ensure contact with air interlock button on tanker helping prevent drive-offs
- change poppet seal without removing the coupler from the hose
- secure to hose with traditional band clamps or built in crimp collar
- 4" MNPT version allows for either cam and groove or threaded flange option
- not intended for liquid service, for vapor recovery *only*



VR4030CS-AL45



VR4040CS-AL

| Coupler Size | Description                           | Aluminum Part #       |
|--------------|---------------------------------------|-----------------------|
| 4"           | 4" coupler x 4" hose shank            | <b>VR4040CS-AL</b>    |
|              | 4" coupler x 3" 45° hose shank        | <b>VR4030CS-AL45</b>  |
|              | 4" coupler x 4" 45° hose shank        | <b>VR4040CS-AL45</b>  |
|              | 4" coupler x 4" 45° hose shank swivel | <b>VR4040CS-ALS45</b> |
|              | 4" coupler x 4" MNPT connection       | <b>VR4040CS-4MNPT</b> |
|              | 4" coupler x 3" hose shank            | <b>VR4030CS-SH</b>    |

## Repair Kits



VRHK

| Description        | Part #             |
|--------------------|--------------------|
| handle kit         | <b>VRHK</b>        |
| compact handle kit | <b>VRHK-C</b>      |
| seal repair kit    | <b>VR4040CSRK1</b> |
| cam arm repair kit | <b>VR4040CSRK2</b> |


## Coupler x Female NPT

- not intended for liquid service, for vapor recovery *only*



## Materials:

- body: cast aluminum
- arms: bronze with stainless steel pins
- finger rings: plated carbon steel
- gasket: Buna-N



| Coupler Size | Female NPT Size | 356T6 Aluminum Part # |
|--------------|-----------------|-----------------------|
| 4"           | 3"              | <b>4030-DVR-AL</b>    |
|              | 4"              | <b>400-DVR-AL</b>     |