

## Disposable In-Line Nipple Filters

### Features:

- for filtration of water, oil and air
- compact and lightweight
- can be installed at point of use
- shape element is conical rather than disc, providing a larger filtering flow and a true, uninterrupted axial flow
- maximum operating pressure: **300 PSI**
- temperature range: **35°F to 300°F (2°C to 148°C)**
- standard 40 micron element ensures minimum pressure drop

Male NPT	Overall Length	Hex	Air Flow	Brass Part #
¼"	1½"	9/16"	20 SCFM	<b>ASP3102-40</b>
½"	2"	7/8"	50 SCFM	<b>ASP3104-40</b>



Pneumatic  
Accessories

## In-Line Lubricator with Filter

### Feature:

- consists of **9076M** particle filter with 40 micron sintered bronze element and **PL400** (3.7 ounce) or **PL400L** (11.0 ounce) lubricator

NPT Size	Oil Capacity	Max. Working Pressure at ambient temperature 70°F (21°C)	Aluminum Part #
¾"	3.7 fluid ozs.	<b>200 PSI</b>	<b>PL400WF</b>
¾"	11.0 fluid ozs.	<b>300 PSI</b>	<b>PL400LWF</b>



## Mini In-Line Lubricators

### Features:

- can be refilled under line pressure
- oil capacity: ¼ fluid ounce
- flow rating: 22 SCFM at 100 PSIG
- maximum operating pressure: **200 PSIG**
- maximum temperature: **150°F (66°C)**

Female NPT Inlet	Outlet	Aluminum Part #
¼"	¼" female NPT	<b>ML200</b>
¼"	¼" male NPT	<b>ML200M</b>
⅜"	⅜" male NPT	<b>ML300M</b>

