

Stainless Panel Builder Gauges

Applications:

- fits industry standard 2.56" panel hole cutout
- suitable for corrosive environments
- used in gaseous and liquid media

Features:

- ASME B40.100 Grade A $\pm 2-1-2\%$ full scale accuracy
- 316L stainless steel wetted parts
- 304 stainless steel case and ring
- white aluminum with black lettering; stop pin
- black aluminum pointer
- glycerin filled case
- laminated safety glass window lens
- ambient temperature range: -4°F to 140°F (-20°C to 60°C)
- maximum media temperature 212°F maximum

PSI Range	Fig. Inter.	Minor Grad.	2½" Face ¼" Lower Back Mount Part #
0-15	3	.2	<i>PBLSS15</i>
0-30	5	.5	<i>PBLSS30</i>
0-60	10	1	<i>PBLSS60</i>
0-100	20	2	<i>PBLSS100</i>
0-160	20	2	<i>PBLSS160</i>
0-200	50	5	<i>PBLSS200</i>
0-300	50	5	<i>PBLSS300</i>
0-400	100	10	<i>PBLSS400</i>
0-600	100	10	<i>PBLSS600</i>
0-800	200	20	<i>PBLSS800</i>
0-1000	200	20	<i>PBLSS1000</i>
0-1500	300	20	<i>PBLSS1500</i>
0-2000	500	50	<i>PBLSS2000</i>
0-3000	500	50	<i>PBLSS3000</i>
0-5000	1000	100	<i>PBLSS5000</i>



Contractor Pressure Gauges

Features:

- accuracy class: $\pm 1\%$ of span
- wetted parts: copper alloy
- window: acrylic, snap in
- dial: aluminum, white
- pointer: aluminum, black, adjustable
- mounting flanged/bracket; rear flange: stainless steel
- case: stainless steel

PSI Range	4½" face, ¼" Lower Mount Part #
0-15	<i>4277750-0001</i>
0-30	<i>4277768-0001</i>
0-60	<i>4277776-0003</i>

