

HS-Series Hydraulic Couplings

Applications:

- designed exclusively for steam applications

Features:

- coupler has a large plated steel sleeve designed for easier gripping with gloves
- special high-temp EPDM O-rings designed for steam service providing a temperature range of -70°F to 400°F (-57°C to 204°C)
- rated to 200 PSI gauge saturated steam 382°F (194°C)



Warning: Do Not Disconnect Under Pressure!

ISO-B Steam Interchange Female Threaded Couplers



Body Size	Threads	Brass		303 Stainless Steel Part #
		Previous Part #	Part #	
1/4"	1/4" - 18 NPTF	B16-200S	2HSF2-B	2HSF2-S
	1/4" - 19 BSPP	---	2HSBF2-B	2HSBF2-S
3/8"	3/8" - 18 NPTF	B16-300S	3HSF3-B	3HSF3-S
	3/8" - 19 BSPP	---	3HSBF3-B	3HSBF3-S
1/2"	1/2" - 14 NPTF	B16-400S	4HSF4-B	4HSF4-S
	1/2" - 14 BSPP	---	4HSBF4-B	4HSBF4-S
3/4"	3/4" - 14 NPTF	B16-600S	6HSF6-B	6HSF6-S
	3/4" - 14 BSPP	---	6HSBF6-B	6HSBF6-S
1"	1" - 11 1/2 NPTF	B16-800S	8HSF8-B	8HSF8-S
	1" - 11 BSPP	---	8HSBF8-B	8HSBF8-S
1 1/2"	1 1/2" - 11 1/2 NPTF	B16-1200S	PS-12HF12-B	---

ISO-B Steam Interchange Female Threaded Plugs



Body Size	Threads	Steel Part #	Brass		303 Stainless Steel Part #
			Previous Part #	Part #	
1/4"	1/4" - 18 NPTF	HS2F2	B17-200S	HS2F2-B	HS2F2-S
	1/4" - 19 BSPP	HS2BF2	---	HS2BF2-B	HS2BF2-S
3/8"	3/8" - 18 NPTF	HS3F3	B17-300S	HS3F3-B	HS3F3-S
	3/8" - 19 BSPP	HS3BF3	---	HS3BF3-B	HS3BF3-S
1/2"	1/2" - 14 NPTF	HS4F4	B17-400S	HS4F4-B	HS4F4-S
	1/2" - 14 BSPP	HS4BF4	---	HS4BF4-B	HS4BF4-S
3/4"	3/4" - 14 NPTF	HS6F6	B17-600S	HS6F6-B	HS6F6-S
	3/4" - 14 BSPP	HS6BF6	---	HS6BF6-B	HS6BF6-S
1"	1" - 11 1/2 NPTF	HS8F8	B17-800S	HS8F8-B	HS8F8-S
	1" - 11 BSPP	HS8BF8	---	HS8BF8-B	HS8BF8-S
1 1/2"	1 1/2" - 11 1/2 NPTF	---	B17-1200S	PS-H12F12-B	---