

## VEP-BOP Series Hydraulic Couplings

## Features:


- red powder coated components and external O-rings for easy BOP service identification
- steel components are plated using ROHS compliant zinc nickel
- blow-out preventer (BOP) coupling critical seals are severe service FKM
- interchangeable with VEP/VEP-HD Series, DNP FSI-BOP Series
- pressure rating **5000 PSI at 70°F (21°C)**
- BOP couplings have been fire tested and Lloyd's certified to **1300°F (700°C)** in accordance with API 16D. Certificate available upon request.



## Female Threaded Couplers

| Body Size | Threads              | Steel Part #        |
|-----------|----------------------|---------------------|
| 3/8"      | 3/8" - 18 NPTF       | <b>3VEPF3-BOP</b>   |
| 1/2"      | 1/2" - 14 NPTF       | <b>4VEPF4-BOP</b>   |
| 3/4"      | 3/4" - 14 NPTF       | <b>6VEPF6-BOP</b>   |
| 1"        | 1" - 11 1/2 NPTF     | <b>8VEPF8-BOP</b>   |
| 1 1/4"    | 1 1/4" - 11 1/2 NPTF | <b>10VEPF10-BOP</b> |
| 1 1/2"    | 1 1/2" - 11 1/2 NPTF | <b>12VEPF12-BOP</b> |

## Female Threaded Plugs



| Body Size | Threads              | Steel Part #        |
|-----------|----------------------|---------------------|
| 3/8"      | 3/8" - 18 NPTF       | <b>VEP3F3-BOP</b>   |
| 1/2"      | 1/2" - 14 NPTF       | <b>VEP4F4-BOP</b>   |
| 3/4"      | 3/4" - 14 NPTF       | <b>VEP6F6-BOP</b>   |
| 1"        | 1" - 11 1/2 NPTF     | <b>VEP8F8-BOP</b>   |
| 1 1/4"    | 1 1/4" - 11 1/2 NPTF | <b>VEP10F10-BOP</b> |
| 1 1/2"    | 1 1/2" - 11 1/2 NPTF | <b>VEP12F12-BOP</b> |