

WS-BOP Series Hydraulic Couplings

Applications:

- designed for use in oil rig BOP systems where couplings are required to operate under fire conditions in an emergency

Features:


- fire tested and Lloyd's certified to **1300°F (700°C)** in accordance with API 16D (Certificate #NAO 0601041/1)
- Contact Dixon® for pressure ratings and other technical information.
- Sleeve is cast using a process that provides better surface finishes, tighter tolerance control, and excellent repeatability.
- Blowout Preventer Couplings are individually marked with the BOP series designation.

High Pressure Wingstyle Female Threaded Couplers

Body Size	Threads	Steel Part #	316 Stainless Steel Part #
3/4"	1/2" - 14 NPTF 3/4" - 14 NPTF	6WSF4-BOP 6WSF6-BOP	--- 6WSF6-SS-BOP
1"	1" - 11½ NPTF	8WSF8-BOP	8WSF8-SS-BOP
1¼"	1¼" - 11½ NPTF	10WSF10-BOP	10WSF10-SS-BOP
1½"	1½" - 11½ NPTF	12WSF12-BOP	12WSF12-SS-BOP
2"	2" - 11½ NPTF	16WSF16-BOP	16WSF16-SS-BOP

**High Pressure Wingstyle Female Threaded Plugs**

Body Size	Threads	Steel Part #	316 Stainless Steel Part #
3/4"	1/2" - 14 NPTF 3/4" - 14 NPTF	WS6F4-BOP WS6F6-BOP	--- WS6F6-SS-BOP
1"	1" - 11½ NPTF	WS8F8-BOP	WS8F8-SS-BOP
1¼"	1¼" - 11½ NPTF	WS10F10-BOP	WS10F10-SS-BOP
1½"	1½" - 11½ NPTF	WS12F12-BOP	WS12F12-SS-BOP
2"	2" - 11½ NPTF	WS16F16-BOP	WS16F16-SS-BOP

**High Pressure Wingstyle Seal Kits**

Body Size	Coupler Style	Repair Kit Contents	FR FKM Part #
3/4"	all	body / valve seals and retaining rings	6BOP-SKIT
1"	all	body / valve seals and retaining rings	8BOP-SKIT
1¼"	all	body / valve seals and retaining rings	10BOP-SKIT
1½"	all	body / valve seals and retaining rings	12BOP-SKIT
2"	all	body / valve seals and retaining rings	16BOP-SKIT

