

T-Series Hydraulic Couplings

Applications:

- Designed for high pressure applications including hydraulic rams and pumps where low flow and pressures up to 10,000 PSI are encountered.

Features:

- interchangeable with Parker 3000 and Enerpac C 604
- nitrile O-ring with TPC-ET back up ring standard providing a temperature range of **-40°F to 250°F (-40°C to 121°C)**
- both poppet valve and ball valve styles available

**Female NPTF Ball Coupler**

Body Size	Threads	Previous Part #	Steel Part #
3/8"	3/8" - 18 NPTF	30-300F	3TF3

**Male NPTF Ball Couplers**

Body Size	Threads	Previous Part #	Steel Part #	Threads	316 Stainless Steel Part #
1/4"	1/4" - 18 NPTF	30-200	2TM2	---	---
3/8"	3/8" - 18 NPTF	30-300	3TM3	3/8" - 18 NPT	3TM3-SS

**Male NPTF Poppet Couplers**

Body Size	Threads	Steel Part #	316 Stainless Steel Part #
3/8"	3/8" - 18 NPT	3TM3-PV	3TM3-SS-PV

**Female NPTF Ball Plugs**

Body Size	Threads	Previous Part #	Steel Part #	Threads	316 Stainless Steel Part #
1/4"	1/4" - 18 NPTF	31-200	T2F2	---	---
3/8"	3/8" - 18 NPTF	31-300	T3F3	3/8" - 18 NPT	T3F3-SS

**Female NPTF Poppet Plugs**

Body Size	Threads	Steel Part #	316 Stainless Steel Part #
3/8"	3/8" - 18 NPT	T3F3-PV	T3F3-SS-PV