

CVV-Series Hydraulic Couplings

Features:

- nitrile (Buna-N) seal standard, providing a temperature range of **-40°F to 250°F (-40°C to 121°C)**
- Contact Dixon® for pressure ratings and other technical information.
- interchangeable with European Screw-Together, Inteva STG-Series, Faster CVV-Series, DNP PVV3, Voswinkel Type-HS

European Female Threaded Couplers

Body Size	Threads	Steel Part #
1/4"	1/4" - 18 NPTF	2CVVF2
	1/4" - 19 BSPP	2CVVBF2
	M14X1.5	2CVVFM1415
3/8"	3/8" - 18 NPTF	3CVVF3
	3/8" - 19 BSPP	3CVVBF3
	M16X1.5	3CVVFM1615
1/2"	1/2" - 14 NPTF	4CVVF4
	3/4" - 16 ORB	4CVVOF4
	1/2" - 14 BSPP	4CVVBF4
	M18X1.5	4CVVFM1815
	7/8" - 14 ORB	4CVVOF5
	M22X1.5	4CVVFM2215
3/4"	3/4" - 14 NPTF	6CVVF6
	3/4" - 14 BSPP	6CVVBF6
	M22X1.5	6CVVFM2215
1"	1" - 11 1/2 NPTF	8CVVF8
	1" - 11 BSPP	8CVVBF8
1 1/4"	1 1/4" - 11 1/2 NPTF	10CVVF10
	1 1/4" - 11 BSPP	10CVVBF10



European Female Threaded Plugs

Body Size	Threads	Steel Part #
1/4"	1/4" - 18 NPTF	CVV2F2
	1/4" - 19 BSPP	CVV2BF2
	M14X1.5	CVV2FM1415
3/8"	3/8" - 18 NPTF	CVV3F3
	3/8" - 19 BSPP	CVV3BF3
	M16X1.5	CVV3FM1615
1/2"	1/2" - 14 NPTF	CVV4F4
	3/4" - 16 ORB	CVV4OF4
	1/2" - 14 BSPP	CVV4BF4
	M18X1.5	CVV4FM1815
	7/8" - 14 ORB	CVV4OF5
	M22X1.5	CVV4FM2215
3/4"	3/4" - 14 NPTF	CVV6F6
	3/4" - 14 BSPP	CVV6BF6
	M22X1.5	CVV6FM2215
1"	1" - 11 1/2 NPTF	CVV8F8
	1" - 11 BSPP	CVV8BF8
1 1/4"	1 1/4" - 11 1/2 NPTF	CVV10F10
	1 1/4" - 11 BSPP	CVV10BF10

