

British Standard Pipe Parallel (BSPP)

Male JIC 37° Flare x Male

Feature:

- pressure rating at 70°F (21°C)

Male JIC 37° Flare	Male BSPP	PSI	Zinc Plated Steel Part #
7/16"-20	¼"-19	5000	B3800-4-4
9/16"-18	⅜"-19	4000	B3800-6-6
¾"-16	½"-14	3000	B3800-8-8
1-1/16"-12	¾"-14	2500	B3800-12-12
1-5/16"-12	1"-11	2000	B3800-16-16



Hydraulic Fittings

Male NPTF x Male

Feature:

- pressure rating at 70°F (21°C)

Male NPTF	Male BSPP	PSI	Zinc Plated Steel Part #
¼"-18	¼"-19	5000	B3401-4-4
⅜"-18	⅜"-19	4000	B3401-6-6
½"-14	½"-14	3000	B3401-8-8
¾"-14	¾"-14	2500	B3401-12-12
1"-11½	1"-11	2000	B3401-16-16



Female NPTF x Male

Feature:

- pressure rating at 70°F (21°C)

Female NPTF	Male BSPP	PSI	Zinc Plated Steel Part #
¼"-18	¼"-19	5000	B3455-4-4
⅜"-18	⅜"-19	4000	B3455-6-6
½"-14	½"-14	3000	B3455-8-8
¾"-14	¾"-14	2500	B3455-12-12
1"-11½	1"-11	2000	B3455-16-16



Male JIC 37° Flare x Male 90° Elbow

Feature:

- pressure rating at 70°F (21°C)

Male JIC 37° Flare	Male BSPP	PSI	Zinc Plated Steel Part #
7/16"-20	¼"-19	5000	B3801-4-4
9/16"-18	⅜"-19	4000	B3801-6-6
¾"-16	½"-14	3000	B3801-8-8
1-1/16"-12	¾"-14	2500	B3801-12-12
1-5/16"-12	1"-11	2000	B3801-16-16



Bonded Dowty Seal for British Thread

Feature:

- pressure rating at 70°F (21°C)

Size	Plated Carbon Steel with Buna O-ring Part #
¼"-19	BDS04
⅜"-19	BDS06
½"-14	BDS08
¾"-14	BDS12
1"-11	BDS16

