

## Domestic Bronze Ball Valves

**Application:**

- for control of air, water, oil and gas in hose or pipe lines, for other services, please contact Dixon®

**Features:**

- pressure rating: **600 PSI** WOG; **150 PSI** saturated steam
- bronze valve bodies, balls and stems
- blow-out proof stems
- glass-filled reinforced PTFE seats and stuffing box ring; stem seals and washers
- plated steel handles and nuts with vinyl sleeves replacements available, contact Dixon® for pricing
- full and standard port valves are repairable
- meets WW-V 35C, Type II Composition



Female NPT	Port	Bronze Part #
1/4"	full	<b>BBV25</b>
3/8"	full	<b>BBV38</b>
1/2"	full	<b>BBV50</b>
3/4"	standard	<b>BBV75</b>
1"	standard	<b>BBV100</b>
1 1/4"	standard	<b>BBV125</b>
1 1/2"	standard	<b>BBV150</b>
2"	standard	<b>BBV200</b>
2 1/2"	standard	<b>BBV250</b>
3"	standard	<b>BBV300</b>

## Domestic Full Port Bronze Ball Valves

**Features:**

- machined solid chrome-plated ball
- multi-fill RPTFE seats and seals
- adjustable packing
- blow-out proof stem design
- bronze castings
- vacuum service to 29 inches Hg
- pressure rating: **600 PSI** WOG; **150 PSI** saturated steam



Female NPT	Port	Bronze Part #
3/4"	full	<b>BBV75FP</b>
1"	full	<b>BBV100FP</b>
1 1/4"	full	<b>BBV125FP</b>
1 1/2"	full	<b>BBV150FP</b>
2"	full	<b>BBV200FP</b>