

## 2-Piece Domestic Stainless Steel Ball Valves

**Features:**

- pressure rating: **1,000 PSI** Cold Working Pressure
- pressure rating: **150 PSI** saturated steam
- vacuum service to 29 inches Hg
- 316 stainless body, ball and stem
- PTFE seal
- blow-out proof stem
- vinyl handle cover
- temperature range: **-40°F to 400°F (-40°C to 204°C)**

Female NPT	Port	316 Stainless Steel Part #
1/4"	full	<b>DSBV25</b>
3/8"	full	<b>DSBV38</b>
1/2"	full	<b>DSBV50</b>
3/4"	full	<b>DSBV75</b>
1"	full	<b>DSBV100</b>
1 1/4"	full	<b>DSBV125</b>
1 1/2"	full	<b>DSBV150</b>
2"	full	<b>DSBV200</b>



Valves

## Stainless Steel Ball Valves Full Port

**Applications:**

- for use with water, oil and gas

**Features:**

- pressure rating: 1/4" - 2" rated to **1000 PSI** WOG (CWP)  
2 1/2" - 3" rated to **800 PSI** WOG (CWP)  
**100 PSI** saturated steam
- 316 stainless steel body, ball and stem
- RPTFE seat, joint gasket and thrust washer
- blow-out proof stem design
- temperature range: **-20°F to 446°F (-29°C to 230°C)** as long as the valve is run fully open/ closed

Female NPT	Port	316 Stainless Steel Part #
1/4"	full	<b>SSBV25</b>
3/8"	full	<b>SSBV38</b>
1/2"	full	<b>SSBV50</b>
3/4"	full	<b>SSBV75</b>
1"	full	<b>SSBV100</b>
1 1/4"	full	<b>SSBV125</b>
1 1/2"	full	<b>SSBV150</b>
2"	full	<b>SSBV200</b>
2 1/2"	full	<b>SSBV250</b>
3"	full	<b>SSBV300</b>

