

Stainless Steel Ball Valves Full Port with Locking Handle

Applications:

- for use with water, oil and gas

Features:

- pressure rating: ¼" - 2" rated to **1000 PSI** WOG (CWP)
2½" - 3" rated to **800 PSI** WOG (CWP)
100 PSI saturated steam
- 316 stainless steel body, ball and stem
- RPTFE seat, joint gasket and thrust washer
- plastic cover on handle
- blow-out proof stem design
- temperature range: **-20°F to 356°F (-29°C to 180°C)**
- lockable
- not recommended as a throttling valve



Female NPT	Port	316 Stainless Steel Part #
¼"	full	SSLBV25
⅜"	full	SSLBV38
½"	full	SSLBV50
¾"	full	SSLBV75
1"	full	SSLBV100
1¼"	full	SSLBV125
1½"	full	SSLBV150
2"	full	SSLBV200
2½"	full	SSLBV250
3"	full	SSLBV300


Stainless Steel Ball Valves Reduced Port with Locking Handle

Applications:

- for use with water, oil and gas

Features:

- pressure rating: **1000 PSI** WOG; **100 PSI** saturated steam
- 316 stainless steel body, ball and stem
- RPTFE seat, joint gasket and thrust washer
- plastic cover on handle
- blow-out proof stem design
- temperature range: **-20°F to 356°F (-29°C to 180°C)**
- lockable
- not recommended as a throttling valve



Female NPT	Port	316 Stainless Steel Part #
¼"	reduced	SSLBV25SP
⅜"	reduced	SSLBV38SP
½"	reduced	SSLBV50SP
¾"	reduced	SSLBV75SP
1"	reduced	SSLBV100SP
1¼"	reduced	SSLBV125SP
1½"	reduced	SSLBV150SP
2"	reduced	SSLBV200SP