B45BY Series Y - Ball Check Valve



47

Applications:

When liquid flows through the valve, the ball is forced into the branch of the valve allowing full
fluid flow. When the liquid stops, equalizing the pressure, the ball drops back into the seat,
preventing backflow. Should reverse flow occur, the differential pressure will cause the ball to
seal firmly against the seat preventing leakage.

Materials:

- ball: PTFE
- product contact surfaces: 316L stainless steel


Features

- two-piece construction
- · replaceable seat
- can be serviced in field (no special tools required)

Specifications:

- operating temperature range: 15°F to 200°F (-9°C to 93°C)
- maximum operating pressure: 150 PSI

Dimensions



Valve Size	Clamp & Cap Size	Ι Δ	В	С	D	Е	F	G	Ball Diameter	Weight (lbs)	316L Stainless Steel Part #
1½"	2"	7.50"	3.30"	1.36"	1.87"	1.98"	2.51"	0.16"	1.6"	4.9	B45BY-R150
2"	2½"	8.50"	3.90"	1.86"	2.33"	2.51"	3.04"	0.16"	2.1"	6.6	B45BY-R200
2½"	3"	10.00"	4.50"	2.37"	2.87"	3.04"	3.57"	0.16"	2.7"	10.5	B45BY-R250
3"	4"	11.50"	5.30"	2.87"	3.83"	3.57"	4.68"	0.16"	3.6"	17.5	B45BY-R300

All dimensions are approximate. Engineering dimensions are available upon request. Specifications are subject to change without notice.

Repair and Seal Kits

Repair kit contains:

- (1) EPDM cap gasket
- (1) PTFE ball
- (1) EPDM/CF8M seat

Seal kit contains:

- (1) EPDM cap gasket
- (1) EPDM/CF8M seat
- FKM seal kit contains:
 - (1) FKM cap gasket
- (1) FKM /CF8M seat

Size	Repair Kit	Seal Kit	FKM Seal Kit	Replacement Ball Only
Size	Part #	Part #	Part #	Part #
1½"	B45BY-RK150	B45BY-SK150	B45BY-SKV150	B45BY-TB150
2"	B45BY-RK200	B45BY-SK200	B45BY-SKV200	B45BY-TB200
2½"	B45BY-RK250	B45BY-SK250	B45BY-SKV250	B45BY-TB250
3"	B45BY-RK300	B45BY-SK300	B45BY-SKV300	B45BY-TB300