

Features:

- recommended for steam service up to **450°F (232°C)**
- easy to seal
- Klingersil® C-4401 washer is inserted between the stem and spud
- leakproof seal forms by rotating the wing nut and hammering it tight
- use with Boss™ clamps found on pages 75 - 76
- use with wing nuts found on page 68

**BOSS™ Washer Seal Couplings with Female Spud**

| Hose Shank x NPT | Plated Steel and / or Iron Part # | 316 Stainless Steel Part # |
|---------------------|--------------------------------------|-------------------------------|
| 3/8" | WF3 | --- |
| 1/2" | WF6 | --- |
| 1/2" x 3/4" | WF26-1 | --- |
| 3/4" | WF26 | RWF26 |
| 1" | WF36 | RWF36 |
| 1 1/4" | WF51 | RWF51 |
| 1 1/2" | WF61 | RWF61 |
| 2" | WF81 ¹ | RWF81 ¹ |
| 2 1/2" | WF96 | --- |
| 3" | WF111 | --- |

¹ not to be used with #250, #275 or #306 Boss™ clamps**BOSS™ Washer Seal Stems**

| Hose Shank x NPT | Plated Steel and / or Iron Part # | Opt Qty | 316 Stainless Steel Part # |
|---------------------|--------------------------------------|---------|-------------------------------|
| 3/8" | SS337 | 100 | --- |
| 1/2" | B1 | 100 | --- |
| 1/2" x 3/4" | B6-1 | 50 | --- |
| 3/4" | B6 | 50 | RB6 |
| 1" | B11 | 50 | RB11 |
| 1 1/4" | B16 | 25 | RB16 |
| 1 1/2" | B21 | 25 | RB21 |
| 2" | B26 ¹ | 10 | RB26 ¹ |
| 2 1/2" | B31 | 5 | --- |
| 3" | B36 | 5 | --- |

¹ not to be used with #250, #275 or #306 Boss™ clamps**BOSS™ Washer Seal Female Spuds**

| Thread Size | Plated Steel and / or Iron Part # | Opt Qty | 316 Stainless Steel Part # |
|-------------|--------------------------------------|---------|-------------------------------|
| 3/8" | CC | 100 | --- |
| 1/2" | B3 | 100 | --- |
| 3/4" | B8 | 25 | RB8 |
| 1" | B13 | 50 | RB13 |
| 1 1/4" | B18 | 25 | RB18 |
| 1 1/2" | B23 | 25 | RB23 |
| 2" | B28 | 10 | RB28 |
| 2 1/2" | B33 | 5 | --- |
| 3" | B38 | 5 | --- |

