

## 500# All Polyester Rack Hose - non-UL Labeled

**Application:**

- for pin rack service / emergency fire fighting only, not to be used for washdown

**Features:**

- outer construction: single jacket, all polyester
- tube construction: clear thermoplastic
- proof pressure: **500 PSI** at ambient temperature **70°F (21°C)**
- service test pressure: **250 PSI** at ambient temperature **70°F (21°C)**
- working pressure: **225 PSI** at ambient temperature **70°F (21°C)**

**Coupled with female and male expansion ring couplings**

Size	Coupling Type	Length	Folded Part #	Coiled Part #
1½"	combo lug, brass NST (NH)	50'	<b>R515-50CBF/F</b>	<b>R515-50CBF</b>
	combo lug, brass NST (NH)	100'	<b>R515100CBF/F</b>	<b>R515100CBF</b>
	combo lug, alum. NST (NH)	50'	<b>R515-50RAF/F</b>	<b>R515-50RAF</b>
	combo lug, alum. NST (NH)	100'	<b>R515100RAF/F</b>	<b>R515100RAF</b>

## 500# Nitrile Covered Fire Hose - Light Duty Red

**Application:**

- ideal for industrial and construction washdown and discharge applications

**Features:**

- outer construction: thin ribbed nitrile
- tube construction: nitrile
- proof pressure: **500 PSI** at ambient temperature **70°F (21°C)**
- service test pressure: **250 PSI** at ambient temperature **70°F (21°C)**
- working pressure: **225 PSI** at ambient temperature **70°F (21°C)**
- other colors, threads and configurations are available, consult Dixon®

**Uncoupled**

Size	Bowl	Length	Part #
1½"	1-13/16"	50'	<b>H515R50UC</b>
2½"	2-13/16"	50'	<b>H525R50UC</b>
1½"	1-13/16"	100'	<b>H515R100UC</b>
2½"	2-13/16"	100'	<b>H525R100UC</b>

**Coupled with female and male expansion ring couplings**

Size	Length	Rocker Lug Aluminum NST (NH) Part #	Rocker Lug Brass NST (NH) Part #	Rocker Lug Aluminum NPSH Part #
1½"	50'	<b>H515R50RAF</b>	<b>H515R50RBF</b>	<b>H515R50RAS</b>
2½"	50'	<b>H525R50RAF</b>	<b>H525R50RBF</b>	<b>H525R50RAS</b>
1½"	100'	<b>H515R100RAF</b>	---	<b>H515R100RAS</b>
2½"	100'	<b>H525R100RAF</b>	---	---

