Fire Fittings & Accessories

Hose Type Booster Hose Couplings

Features:

- · special tooling is required to attach these couplings to hose
- · hardcoat finish
- · complete set
- working pressure: 800 PSI at ambient temperature 70°F (21°C)
- ¾ and 1" NST threads are the same size; also known as Chemical Hose Thread (CHT) or Booster Hose Thread

Hose Size	Thread Type	Bowl Size	Aluminum Hardcoat Part #
3/4"	1" NPSH	1-1/4"	ABH08125
1"	1" NST (NH)	1-7/16"	ABH10143F
1"	1" NST (NH)	1-1/2"	ABH10150F



Forged Forestry Couplings

Features:

- maximum operating pressure: 300 PSI at ambient temperature 70°F (21°C)
- common quarter turn sexless head (a 1½" QT fitting will mate with a ¾" QT or 1" QT)

	1/4 Turn Male
Thread	Forged Aluminum
Tilleda	Part #
¾" GHT	QTM75GHT-F
1" NPSH	QTM100S-F
1" NPT	QTM100T-F
1½" NST (NH)	QTM150F-F
1½" NPT	QTM150T-F
	1/4 Turn Female



	/4 Tutti i citiale
Thread	Forged Aluminum Part #
¾" GHT	QTF75GHT-F
1" NPSH	QTF100S-F
1" NPT	QTF100T-F
11/2" NST (NH)	QTF150F-F
1½" NPT	QTF150T-F



Forestry Coupling Gasket		
Part #		
QTG-F		



Quick Connect Forestry Expansion Ring Couplings

• sold in sets of (2) with expansion ring

Hose Size	Bowl Size	Forged Aluminum Part #
1½"	1-11/16"	QTX150-F

