Fire Fittings Accessories

SSA - Storz x Storz Adapter

Features:

- anodized components per MIL-A-8625 Type III Class 1
- · Buna-N gaskets
- working pressure: 150 PSI at 70°F (21°C)
- cast aluminum lock lever assembly on 4", 5" and 6"

Storz Size	Storz Size	6061-T6 Forged Alumium Part #	
1½"	2"	SSA1520	
1 1/2	2½"	SSA1525	
2"	2½"	SSA2025	
	3"	SSA2030	
	4"	SSA2540	
4"	5"	SSA4050	
	6"	SSA4060	
5"	6"	SSA5060	



SSA30 - Storz x Storz 30° Elbow Adapters

Features:

- anodized components per MIL-A-8625 Type III Class 1
- Buna-N gaskets
- working pressure: 150 PSI at 70°F (21°C)
- cast aluminum lock lever assembly on 4", 5" and 6"

Storz Size	Storz Size	6061-T6 Forged Alumium Part #
5"	5"	SSA30-550



Dixon Storz Hydrant Conversion Adapters

Features:

- designed to adapt 41/2" NH threads found on most hydrants to Storz connection
- secured to hydrant by 3 set screws positioned around the rim
- · hydrant side: metal face to seal to gasketed face on hose
- · reflective stripe around the rim for ease of night time location

Size	Part #
5" Storz x 41/2" NH (NST)	SHA5045F

