

Bayloc™ Dry Disconnect Vapor Adapter x Female NPSM



Female NPSM	Adapter Size	Seal	Max PSI at 70°F (21°C)	Stainless Steel ¹ Part #
1½"	2"	PTFE	150	DBAV73-2030

¹ stainless steel corrosion resistance is equivalent to 304 stainless steel

Note: Reference page 179 for dust caps for adapters

Cam & Groove Actuator Style Couplers

Applications:

- suited for vapor recovery, suction pump line and other applications where it is necessary to easily drain the hose or pipe for cleaning
- can also be used when product retention in a hose or pipe is desired and damage from accidental spill from an open coupler is not a concern
- couplers work with the DBA popped adapters on page 7 in applications where automatic closure for the coupler is not desired

Materials:

- 316 stainless steel body
- 304 stainless steel internal components
- replacement parts are available, contact Dixon® for more information

Features:

- EZ Boss-Lock™ cam arms
- stainless steel locking lever standard
- use with standard cam and groove dust plugs sized one size larger than the dry disconnect size
- prevents spillage from normal and accidental disconnection of the connection



Female NPT	Coupler Size	Seal Material	Stainless Steel Part #
1½"	2"	<i>Buna</i>	D2C71-150
2"	2½"		D2C71-200
1½"	2"	<i>FKM</i>	D2C72-150
2"	2½"		D2C72-200
1½"	2"	<i>PTFE Encapsulated Silicone</i>	D2C73-150
2"	2½"		D2C73-200
1½"	2"	<i>EPDM</i>	D2C74-150
2"	2½"		D2C74-200
1½"	2"	<i>PTFE Encapsulated FKM</i>	D2C77-150
2"	2½"		D2C77-200
1½"	2"	<i>FKM-B</i>	D2C79-150
2"	2½"		D2C79-200