## Double Clapper Concealed Type Siamese Assemblies (U)C






# Acc

#### Features:

- fully reversible with a perpendicular trunnion allowing one body to be installed for top and bottom connections
- branded: 'standpipe', 'auto-spkr', 'auto-spkr.-standpipe'
- finishes: -P polished or -C polished chrome plated
- maximum operating pressure: 250 PSI
- complete unit consisting of the following six parts: (1) 4025REV90, or 4030REV90, or 90CREV6025, (1) 24-385 plate, (2) 23-270 double female connections, (2) 17-127 plugs with chains

Outlet Female NPT Thread	(2) Inlets Female NST (NH) Thread	Branding	Cast Brass Part #
4"	2½"	AutoSprinkler	2WCA4025F-P
4"	21/2"	StandPipe	2WCA4025F-SP-P
4"	2½"	AutoSprinkler	2WCA4025F-C
4"	2½"	StandPipe	2WCA4025F-SP-C
4"	3"	AutoSprinkler	2WCA4030F-P
6"	2½"	AutoSprinkler	2WCA6025F-P
6"	21/2"	StandPipe	2WCA6025F-SP-P
6"	2½"	AutoSprinkler	2WCA6025F-C
6"	2½"	StandPipe	2WCA6025F-SP-C











# **Two Way Sidewalk Siamese Assemblies**







## Features:

- UL listed, FM approved
- finishes: -P polished or -C polished chrome plated
- complete unit consists of: (1) 21-133 90° Siamese body, double clapper, (2) 17-127 pin lug plugs with chains, (1) 23-404 sleeve, (1) 24-405 escutcheon plate

Outlet	(2) Inlets	Cast Brass
Female NPT Thread	Female Thread	Part #
4"	2½"	2WSA4025F
4"	2½"	2WSA4025F-SP
6"	2½"	2WSA6025F
6"	2½"	2WSA6025F-SP

### **Dimensions**

Size	А	В	С	E	F
4" x 2½" x 2½"	9¼"	10%"	10¾"	10%"	65/8"
6" x 2½" x 2½"	11¼"	10½"	11¾"	13"	71/4"

Note: some components UL listed/FM approved, not entire assembly

