

## Global Cast Angle Valves

**Features:**

- NPT inlet thread only
- aluminum handwheel
- working pressure: **300 PSI at 70°F (21°C)**
- UL listed and FM approved
- New York City Board of Standards and Appeals, approval # MEA 54-07-E
- available finishes:
  - cast (standard)
  - polished: -P
  - chrome: -C
  - minimum quantity for special thread, consult Dixon®

**Female Inlet**

Inlet Female NPT	Outlet Male Thread	Cast Yellow DZR Brass Part #
1½"	1½" male NST (NH)	<b>AV150-I</b>
2½"	2½" male NST (NH)	<b>AV250-I</b>
2½"	2½" MNYFD	<b>AV250NYFD-I</b>

**Double Female****Features:**

- NPT inlet and outlet
- aluminum handwheel
- working pressure: **300 PSI at 70°F (21°C)**
- New York City Board of Standards and Appeals, approval # MEA 54-07-E
- available finish:
  - cast (standard)
  - polished = -P
  - chrome = -C

Inlet Female NPT	Outlet Female NPT	Cast Yellow DZR Brass Part #
1½"	1½"	<b>AVF150-I</b>
2½"	2½"	<b>AVF250-I</b>

**Dimensions**

Size	A	B	C closed	C open	D	E	Wt. in Lbs.
1½"	4.13"	3.75"	6.80"	7.78"	2.25"	1.81"	4.4
2½"	5.69"	5.00"	9.00"	10.72"	3.19"	2.59"	9.5

