Water-Steam Washdown Station

Application:

• fail-safe mixing station safely blends steam and cold water for hot water on demand, should cold water fail, the steam is instantly shut-off

Features:

•

- globe style control valves
- dial thermometer
- in-line check valves
- ³/₄" inlet and outlet
- stainless steel hose rack
- · mounting plate and hardware for wall mounting
- maximum operating pressure: 150 PSI
 - maximum temperature: 200°F (93°C)

Bronze
Part #
SWDS

Pressure Requirements

Steam Pressure		Water Pressure	
Minimum	Maximum	Minimum	Maximum
80 PSI	90 PSI	50 PSI	80 PSI

Hot and Cold Water Mixing Station



station is not supplied with hose and nozzle

with hose and nozzle

Features:

- · globe style control valves
- in-line check valves
- ¾" inlet and outlet
- stainless steel hose rack
- mounting plate and hardware for wall mounting
- maximum operating pressure: 150 PSI
- maximum temperature: 200°F (93°C)

Rack for Mixing Station



- Features:
- stainless steel lag screws
- solid brass mounting crowns
- supplied with mounting hardware
- rack fits SWDS and WDS1 mixing stations
- holds 50' of ¾" heavy duty industrial grade hose

Stainless Steel Part # **WDSR**