

Pressure Washing

Fixed Plugs

Features:

- working pressure: **3650 PSI**
- **7.8 GPM**
- maximum temperature: **300°F (149°C)**



1/4" fixed quick coupling plugs

Description	Part #
1/4" female x 22 mm x 1.5 mm male	AL454 ¹

¹ for use with **AL453** and **AL9**

Description	Part #
1/4" male x 22 mm x 1.5 mm male	AL455F ²

² for use with **AL462** only

3/8" fixed quick coupling plugs



Description	Part #
3/8" female x 22 mm x 1.5 mm male	AL456 ¹

¹ for use with **AL453** and **AL9**

Description	Nickel Plated Brass Part #
3/8" female x male plug	AL464 ²

² for use with **AL462** only

Injector Nozzles

Features:

- designed to inject cleaning solutions into high pressure discharge lines
- 3/8" male inlet and outlet
- maximum working pressure: **4000 PSI**



AL477

Description	Orifice	Flow (GPM)	Part #
adjustable, green	1.8 mm	2 - 3	AL472
adjustable, red	2.1 mm	3 - 4	AL477
adjustable, blue	2.3 mm	4 - 5.5	AL478

Line Strainer

Features:

- working pressure: **100 PSI**
- 1/2" female inlet, 1/2" male outlet
- .60 mesh cuffed filter
- 2 additional 1/4" side ports
- **8 GPM** maximum



Aluminum
Part #

AR3000-A2