Nitrile Washdown Hose

Application:

 ideal for industrial, agricultural, chemical and construction washdown and discharge applications, not for firefighting



Feature:

· resistant to weather and abrasion

Coupled with NPSH female and male King™ short shank couplings, crimp sleeve, aluminum shank with brass pin lug swivel nut

Size	Length	Part #
1½"	25' 50'	WDH15BK25KAS WDH15BK50KAS
2"	25' 50'	WDH20BK25KAS WDH20BK50KAS
2½"	25' 50'	WDH25BK25KAS WDH25BK50KAS
3"	25' 50'	WDH30BK25KAS WDH30BK50KAS



Coupled with NST (NH) female and male King™ short shank couplings, crimp sleeve, aluminum shank with brass pin lug swivel nut

	Size	Length	Part #
•	1½"	25' 50'	WDH15BK25KAF WDH15BK50KAF
	2½"	25' 50'	WDH25BK25KAF WDH25BK50KAF



Coupled with female and male (C & E) global aluminum cam and groove, crimp sleeve

Size	Length	Part #
1½"	25'	WDH15BK25GAX
	50'	WDH15BK50GAX
2"	25'	WDH20BK25GAX
	50'	WDH20BK50GAX
2½"	25'	WDH25BK25GAX
∠⁄⁄2	50'	WDH25BK50GAX
3"	25'	WDH30BK25GAX
3"	50'	WDH30BK50GAX
4"	25'	WDH40BK25GAX
4	50'	WDH40BK50GAX



