

Nitrile Washdown Hose

Application:

- ideal for industrial, agricultural and construction washdown and discharge applications, not for firefighting

**Feature:**

- resistant to weather and abrasion

Uncoupled

| Size | Color | Bowl | Length | Working Pressure | Part # |
|------|--------|----------|--------|------------------|---------------------|
| 1" | black | 1¼" | 50' | 200 PSI | <i>WDH10BK50UC</i> |
| | black | 1¼" | 100' | | <i>WDH10BK100UC</i> |
| | yellow | 1¼" | 100' | | <i>WDH10Y100UC</i> |
| | blue | 1¼" | 100' | | <i>WDH10BL100UC</i> |
| 1½" | black | 1-13/16" | 50' | | <i>WDH15BK50UC</i> |
| | black | 1-13/16" | 100' | | <i>WDH15BK100UC</i> |
| 2" | black | 2-5/16" | 50' | | <i>WDH20BK50UC</i> |
| | black | 2-5/16" | 100' | | <i>WDH20BK100UC</i> |
| 2½" | black | 2-13/16" | 50' | | <i>WDH25BK50UC</i> |
| | black | 2-13/16" | 100' | | <i>WDH25BK100UC</i> |
| 3" | black | 3¾" | 50' | 150 PSI | <i>WDH30BK50UC</i> |
| | black | 3¾" | 100' | | <i>WDH30BK100UC</i> |
| 4" | black | 4¾" | 50' | | <i>WDH40BK50UC</i> |
| | black | 4¾" | 100' | | <i>WDH40BK100UC</i> |
| 6" | black | 6¾" | 50' | | <i>WDH60BK50UC</i> |
| | black | 6¾" | 100' | | <i>WDH60BK100UC</i> |



Hot Water Washdown Hose

Features:

- smooth extruded Chlorobutyl tube
- white, wrapped Hypalon cover (.075" thick) with braided textile reinforcement
- furnished with internal stainless steel spring guards at both ends
- ¾" male on one end and ½" male on the other
- working pressure: **250 PSI**
- maximum temperature: **200°F (93°C)**



| Hose ID x Length | Part # |
|------------------|-------------------|
| 5/8" x 25' | <i>SWDSHOSE25</i> |
| 5/8" x 50' | <i>SWDSHOSE50</i> |

Pressure Washer Braided Hose

Feature:

- maximum temperature: **250°F (121°C)**

| ID | Male Swivel Inlet | Male Swivel Outlet | Pressure Rating (PSI) | Length | Rubber Part # |
|------|-------------------|--------------------|-----------------------|--------|--------------------|
| 3/8" | 3/8" | 3/8" | 4,000 | 50' | <i>AR503830SSP</i> |

