

Spiral Hose and Cable Protection

**Application:**

- used in mining, quarrying, forestry, offshore industries and most hydraulic hose applications

**Features:**

- crush and high abrasion resistance
- chemical and UV ray resistant
- self-lubricating to reduce hose wear
- easy to install on-site
- smooth radius on all edges
- can be used on single or multiple hose bundles
- spiral guard ID is equal to the guard at rest
- sold in coil lengths only

**Flame Retardant Product**

**Features:**

- approved by MSHA #1C-264/0
- tested to: AS 2600, AS1180.10B, AS 1180.13A
- flame retardant, self extinguishing, anti static
- temperature range: **-148°F to 262°F (-100°C to 128°C)**
- color: black



Nominal ID	Coil Length	OD Range (inches)	Part #
0.45"	66'	.47" to .86"	<b>FRSGX16</b>
0.55"	66'	.62" to 1.06"	<b>FRSGX20</b>
0.80"	66'	.86" to 1.37"	<b>FRSGX25</b>
1.00"	66'	1.06" to 1.69"	<b>FRSGX32</b>
1.26"	66'	1.30" to 2.17"	<b>FRSGX40</b>
1.50"	66'	1.65" to 2.52"	<b>FRSGX50</b>
2.00"	66'	2.05" to 2.95"	<b>FRSGX63</b>
2.40"	66'	2.56" to 3.80"	<b>FRSGX75</b>
2.83"	66'	3.15" to 4.30"	<b>FRSGX90</b>
3.43"	33'	3.80" to 4.90"	<b>FRSGX110</b>

**Standard Product**

**Features:**

- not flame retardant
- temperature range: **-40°F to 248°F (-40°C to 120°C)**



Nominal ID	Coil Length	OD Range (inches)	Part #
0.45"	66'	.47" to .86"	<b>NFSGX16</b>
0.55"	66'	.62" to 1.06"	<b>NFSGX20</b>
0.80"	66'	.86" to 1.37"	<b>NFSGX25</b>
1.00"	66'	1.06" to 1.69"	<b>NFSGX32</b>
1.26"	66'	1.30" to 2.17"	<b>NFSGX40</b>
1.50"	66'	1.65" to 2.52"	<b>NFSGX50</b>
2.00"	66'	2.05" to 2.95"	<b>NFSGX63</b>
2.40"	66'	2.56" to 3.80"	<b>NFSGX75</b>
2.83"	66'	3.15" to 4.30"	<b>NFSGX90</b>
3.43"	33'	3.80" to 4.90"	<b>NFSGX110</b>
4.48"	40'	4.50" to 5.50"	<b>NFSGX125</b>
5.07"	27'	<b>NEW</b> 4.80" to 6.00"	<b>NFSGX140</b>
5.87"	20'	5.70" to 7.00"	<b>NFSGX160</b>