

Series 1 Micro-Fog Lubricator with High Pressure Sight Feed Dome

Application:


- Designed for use with alcohol or other anti-freeze agents when units are installed in cold temperature environments.
- Micro-fog lubricators are used for applications containing one or more points of lubrication, cylinders and multiple or single tools.
- Air flow through the lubricator lifts oil from the reservoir to the sight-feed dome. Oil is dropped into the fog generator and atomized into a fine mist. Lightweight particles are delivered downstream for lubrication. Heavier particles fall back into the reservoir.

Features:

- high pressure sight feed dome with aluminum case and fluorocarbon O-rings and seals; high pressure sight glass on bowls and metal petcock drain
- The micro-fog lubricator delivers 10% of the oil drops visible through the transparent sight-feed dome.



Micro-fog lubricators cannot be filled under pressure.



Features:


- 4 oz. reservoir
- in-line or modular installation
- quick release bayonet bowl
- micro-fog design delivers aerosol mist
- recommended lubricants: misting type oil rated 50 to 200 SSU (ISO Grade 7 to 46) at 100°F
- inlet pressure: **250 PSI**
- maximum temperature: **175°F**

Compact

Port Size	Flow (SCFM)	Metal Bowl with Sight Glass Part #	Price/E
1/4"	60	L73M-2MBPX	\$275.30
3/8"	60	L73M-3MBPX	295.15
1/2"	60	L73M-4MBPX	297.95



metal bowl



** Optional pexex sight-feed dome.
† Minimum clearance required to remove bowl.

Features:


- 7 oz. reservoir
- in-line or modular installation
- quick release bayonet bowl
- micro-fog design delivers aerosol mist
- recommended lubricants: misting type oil rated 50 to 200 SSU (ISO Grade 7 to 46) at 100°F
- inlet pressure: **250 PSI**
- maximum temperature: **175°F**

Standard

Port Size	Flow (SCFM)	Metal Bowl with Sight Glass Part #	Price/E
3/8"	114	L74M-3MBPX	\$363.95
1/2"	154	L74M-4MBPX	363.95
3/4"	142	L74M-6MBPX	314.30



metal bowl



1 quart US (1 liter) reservoir
1/4 turn drain

Features:

- 1 qt. reservoir
- oil level sight gauge
- particle removal per ISO 8573-1, class 5 and class 3
- one turn threaded bowl attachment permits easy maintenance
- inlet pressure: **250 PSI**
- maximum temperature: **175°F**

Jumbo

Port Size	Flow (SCFM)	Metal Bowl with Sight Glass Part #	Price/E
1"	275	L17-800APX	\$415.70



metal bowl

See pages 265-266 for lubricator accessories. See page 156 for air tool lubricant.



FRL's are designed for air service only, unless otherwise indicated.

SCFM ratings given at 90 PSIG inlet pressure.